




PROJECT NAME:-

THE ROYALS PALACE

DEVELOPER NAME :-

SHREE RAM INFRA

GENERAL NOTES:-

- ALL DIMENSION AND LEVEL ARE IN FEET & INCHES
- DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSION ONLY.
- THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVANT ARCHITECTURAL AND SERVICE DRAWING ANY DISCREPANCY SHOULD BE IMMEDIATELY BROUGHT TO NOTICE.
- ONLY LOAD BEARING WALLS ARE SHOWN IN PLAN OTHER WALLS SHALL BE STOPPED 1/2" BELOW SOFFIT OF BEAM/SLAB AND GAP FILLED WITH LEAN CEMENT MORTAR UNLESS OTHERWISE SHOWN IN ARCHITECTURAL DRAWING.

REINFORCEMENT DETAILS

- HIGH YIELD STRENGTH DEFORMED BARS MARKED AS Ø WITH CHARACTERISTIC STRENGTH 500 N/MM CONFORMING TO IS 1786-2008, SHALL BE USED.
- LAP IN SLAB & BEAMS OF SUPER STRUCTURE CLOSE TO MID SPAN FOR BOTTOM BARS & CLOSE TO SUPPORT FOR TOP BARS SHALL BE AVOIDED.
- LAP SHALL BE STAGGERED SO THAT NO MORE THAN 1/2 OF BARS SHALL BE LAPPED AT ANY SECTION
- LAP LENGTH FOR HIGH YIELD STRENGTH DEFORMED BARS SHALL BE AS FOLLOW, WHERE Ø IS DIA OF BARS.

CONC.GRADE	Ldt
M-20	57Ø
M-25	49Ø
M-30	45Ø
M-35	40Ø

- TIES OR DISTRIBUTION REINFORCEMENT IN THE SLAB SHALL BE PROVIDED OF 8Ø@8"C/C OTHERWISE MENTIONED.

CONCRETE DETAILS

- NOMINAL SIZE OF CRUSHED STONE GRADED AGGR-GATE SHALL BE 3/4" UNLESS OTHERWISE STATED.
- GRADE OF CONCRETE SHALL BE M-25 CONFORMING TO IS 456-2000 UNLESS OTHERWISE NOTED.
- CLEAR COVER OF CONCRETE IN INCHES TO THE MAIN REINFORCEMENT UNLESS SPECIFIED OTHERWISE SHALL BE :-

PARTICULAR	BOTTOM	TOP	SIDES
FOOTING	50mm	50mm	50mm
COLUMNS/ S WALLS			40mm
RETAINING WALL		25mm	40mm (EARTH SIDE)
			20mm (IN SIDE)
BEAMS, LINTEL	25mm	25mm	25mm
SLAB	20mm	15mm	25mm (WHERE APPLICABLE)
WATER TANK (WALL & SLAB)			25mm (ON WATER FACE)
			40mm (ON EARTH SIDE)

MISCELLANEOUS

- REMOVAL OF SHUTTERING:- THIS SHALL BE AS UNLESS OTHERWISE STATED.
 - WALL, COL & VERTICAL FACE OF ALL MEMBERS 24 TO 48 HOURS.
 - SLABS (PROPS LEFT UNDER) ----- 3 DAYS.
 - BEAM SOFFITS (PROPS LEFT) ----- 7 DAYS.
 - REMOVAL OF PORPS UNDER SLAB ----- 7 DAYS.
 - SPAN UP TO 4.5 METER ----- 14 DAYS.
 - SPAN OVER TO 6.0 METER ----- 21 DAYS.
- SPACER BERS:- SHALL BE 20MM DIA AS MAX. 4'-0"(1200) INTERVALS

DESIGN DATA:-

GRADE OF CONCRETE SHALL BE M-25.
GRADE OF STEEL SHALL BE Fe-550 D (Primary Producers Only)

DESIGN FOR :-

BUILDING DESIGN FOR B+S+G+5
SBC =12 MT/Sq.M@3.0M

PROJECT:	PROPOSED RESIDENTIAL BUILDING ON PLOT NO. -45 SCHEME -24 (RAJAT VIHAR), JAIPUR		
DRAWING TITLE:	COLUMN LAYOUT		
ARCHITECTS:	4 INSIDE ARCHITECTURE N INTERIORS Plot no. 72, S.P. Marg., C- Scheme jaipur, rajasthan, India cont: +91 9950595991, 91 9982812777 e.mail: jeets.arch@gmail.com		
DRAWN BY:	SUNNY	DRAWING. NO.	SDC-4IN-MPR45-01
CHECKED BY:	RAHUL	REVISION NO.	R-00
SCALE:	N.T.S.	DATE:	JUNE.14/2024

STRUCTURAL CONSULTANT:



SHYAM DESIGN CONSULTANTS
ER. RAHULSHARMA [M.Tech Str.]
M: 968045482, 9929039105
Email: shyamdesignconsultants1211@gmail.com

1. ALL DIMENSION AND LEVEL ARE IN FEET & INCHES
2. DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSION ONLY.
3. THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVANT ARCHITECTURAL AND SERVICE DRAWING ANY DISCREPANCY SHOULD BE IMMEDIATELY BROUGHT TO NOTICE.
4. ONLY LOAD BEARING WALLS ARE SHOWN IN PLAN OTHER WALLS SHALL BE STOPPED 1/2" BELOW SOFFIT OF BEAM/SLAB AND GAP FILLED WITH LEAN CEMENT MORTAR UNLESS OTHERWISE SHOWN IN ARCHITECTURAL DRAWING.

1. HIGH YIELD STRENGTH DEFORMED BARS MARKED AS Ø WITH CHARACTERISTIC STRENGTH 500 N/MM CONFORMING TO IS 1786-2008 SHALL BE USED.
2. LAP IN SLAB & BEAMS OF SUPER STRUCTURE CLOSE TO MID SPAN FOR BOTTOM BARS & CLOSE TO SUPPORT FOR TOP BARS SHALL BE AVOIDED.
3. LAP SHALL BE STAGGERED SO THAT NO MORE THAN 1/2 OF BARS SHALL BE LAPPED AT ANY SECTION
4. LAP LENGTH FOR HIGH YIELD STRENGTH DEFORMED BARS SHALL BE AS FOLLOW. WHERE Ø IS DIA. OF BARS.

5. TIES OR DISTRIBUTION REINFORCEMENT IN THE SLAB SHALL BE PROVIDED OF 8@8"C/C OTHERWISE MENTIONED.

1. NOMINAL SIZE OF CRUSHED STONE GRADED AGGR-GATE SHALL 3/4" UNLESS OTHERWISE STATED.
2. GRADE OF CONCRETE SHALL BE M-25 CONFORMING TO IS 456-20 UNLESS OTHERWISE NOTED.
3. CLEAR COVER OF CONCRETE IN INCHES TO THE MAIN REINFORCEMENT UNLESS SPECIFIED OTHERWISE SHALL BE :-

MISCELLANEOUS

1. REMOVAL OF SHUTTERING:- THIS SHALL BE AS UNLESS OTHERWISE STATED.
- * WALL, COL & VERTICAL FACE OF ALL MEMBERS 24 TO 48 HOURS.
 - * SLABS (PROPS LEFT UNDER) ----- 3 DAYS.
 - * BEAM SOFFITS (PROPS LEFT) ----- 7 DAYS.
 - * REMOVAL OF PORPS UNDER SLAB ----- 7 DAYS.
 - SPAN UP TO 4.5 METER ----- 14 DAYS
 - SPAN OVER TO 6.0 METER ----- 21 DAYS.
2. SPACER BERS:- SHALL BE 20MM DIA AS MAX.
40-0' (120') INTERVALS



GRADE OF CONCRETE SHALL BE M-25.
GRADE OF STEEL SHALL BE Fe-550 D (Primary Producers Only)


BUILDING DESIGN FOR B+S+G+5
SBC = 12 MT/Sq.M@3.0M

STRUCTURAL CONSULTANT:

DEVELOPER NAME :-
SHREE RAM INFRA

5th Floor (I) To Terrace Floor (I)	SIZE	9'x90"		SIZE	9'x39"		SIZE	9'x42"	
	REINF.	44#12		REINF.	12#16 +6#12		REINF.	8#16 +12#12	
4th Floor (I) To 5th Floor (I)	SIZE	9'x90"		SIZE	9'x39"		SIZE	9'x42"	
	REINF.	44#12		REINF.	18#16		REINF.	20#16	
3rd Floor (I) To 4th Floor (I)	SIZE	9'x90"		SIZE	9'x39"		SIZE	9'x42"	
	REINF.	44#12		REINF.	4#20 +14#16		REINF.	8#20 +12#16	
2nd Floor (I) To 3rd Floor (I)	SIZE	9'x90"		SIZE	9'x39"		SIZE	9'x42"	
	REINF.	44#12		REINF.	12#20 +6#16		REINF.	20#20	
1st Floor (I) To 2nd Floor (I)	SIZE	9'x90"		SIZE	9'x39"		SIZE	9'x42"	
	REINF.	44#12		REINF.	18#20		REINF.	8#25 +10#20	
Ground Floor (I) To 1st Floor (I)	SIZE	9'x90"		SIZE	9'x39"		SIZE	9'x42"	
	REINF.	8#16 +36#12		REINF.	8#25 +10#20		REINF.	20#25	
Footing To Ground Floor (I)	SIZE	9'x90"		SIZE	12'x39"		SIZE	18'x42"	
	REINF.	20#16 +24#12		REINF.	8#25 +12#20		REINF.	24#25	
WALL			SW-1/SW-3/SW-6/SW-7.			SW-2/SW-5.			SW-4.





RAFT TOP PEDESTAL LAYOUT


RAFT CONTINUOUS(MAIN) REINFORCEMENT DETAILS:

1. RAFT BOTTOM OUTER BARS PARALLEL TO X- DIRECTION = #12@8"C/C (LAYER-1)
2. RAFT BOTTOM INNER BARS PARALLEL TO Y- DIRECTION = #12@8"C/C (LAYER-2)
3. RAFT TOP INNER BARS PARALLEL TO Y- DIRECTION = #12@8"C/C (LAYER-3)
4. RAFT TOP OUTER BARS PARALLEL TO X- DIRECTION = #12@8"C/C (MAIN) (LAYER-4)

RAFT THICKNESS = D-27" UNLESS SPECIFIED

LIFT PIT RAFT THICKNESS = D-33" UNLESS SPECIFIED

1. LIFT PIT BOTTOM THRU. BARS PARALLEL TO X & Y DIRECTION = #20@4"C/C
1. LIFT PIT TOP THRU. BARS PARALLEL TO X & Y DIRECTION = #16@8"C/C



LEGENDS OTHERS.

- EARTH FILLING
- LIFT PIT LVL @ B.F.L LVL
- FOOTING @ B.F.L LVL
- R.C.C WALL @ LIFT PIT LVL
- LIFT PIT LVL @ N.G.L LVL



PROJECT NAME:-

THE ROYALS PALACE

DEVELOPER NAME :-

SHREE RAM INFRA

GENERAL NOTES:-

1. ALL DIMENSION AND LEVEL ARE IN FEET & INCHES
2. DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSION ONLY.
3. THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVANT ARCHITECTURAL AND SERVICE DRAWING ANY DISCREPANCY SHOULD BE IMMEDIATELY BROUGHT TO NOTICE.
4. ONLY LOAD BEARING WALLS ARE SHOWN IN PLAN OTHER WALLS SHALL BE STOPPED 1/2" BELOW SOFFIT OF BEAM/SLAB AND GAP FILLED WITH LEAN CEMENT MORTAR UNLESS OTHERWISE SHOWN IN ARCHITECTURAL DRAWING.

REINFORCEMENT DETAILS

1. HIGH YIELD STRENGTH DEFORMED BARS MARKED AS Ø WITH CHARACTERISTIC STRENGTH 500 N/MM CONFORMING TO IS 1786-2008, SHALL BE USED.
2. LAP IN SLAB & BEAMS OF SUPER STRUCTURE CLOSE TO MID SPAN FOR BOTTOM BARS & CLOSE TO SUPPORT FOR TOP BARS SHALL BE AVOIDED.
3. LAP SHALL BE STAGGERED SO THAT NO MORE THAN 1/2 OF BARS SHALL BE LAPPED AT ANY SECTION
4. LAP LENGTH FOR HIGH YIELD STRENGTH DEFORMED BARS SHALL BE AS FOLLOW, WHERE Ø IS DIA OF BARS.

CONC GRADE	Ldt
M-20	570
M-25	490
M-30	450
M-35	400

5. TIES OR DISTRIBUTION REINFORCEMENT IN THE SLAB SHALL BE PROVIDED OF 80@8"C/C OTHERWISE MENTIONED.

CONCRETE DETAILS

1. NOMINAL SIZE OF CRUSHED STONE GRADED AGGR-GATE SHALL BE 3/4" UNLESS OTHERWISE STATED.
2. GRADE OF CONCRETE SHALL BE M-25 CONFORMING TO IS 456-2000 UNLESS OTHERWISE NOTED.
3. CLEAR COVER OF CONCRETE IN INCHES TO THE MAIN REINFORCEMENT UNLESS SPECIFIED OTHERWISE SHALL BE :-

PARTICULAR	BOTTOM	TOP	SIDES
FOOTING	50mm	50mm	50mm
COLUMNS/ S WALLS			40mm
RETAINING WALL		25mm	40mm (EARTH SIDE) 20mm (IN SIDE)
BEAMS, LINTEL	25mm	25mm	25mm
SLAB	20mm	15mm	25mm (WHERE APPLICABLE)
WATER TANK (WALL & SLAB)			25mm (ON WATER FACE) 40mm (ON EARTH SIDE)

MISCELLANEOUS

1. REMOVAL OF SHUTTERING:- THIS SHALL BE AS UNLESS OTHERWISE STATED.
 - * WALL, COL & VERTICAL FACE OF ALL MEMBERS 24 TO 48 HOURS.
 - * SLABS (PROPS LEFT UNDER) ----- 3 DAYS.
 - * BEAM SOFFITS (PROPS LEFT) ----- 7 DAYS.
 - * REMOVAL OF PORPS UNDER SLAB ----- 7 DAYS.
 - SPAN UP TO 4.5 METER ----- 14 DAYS.
 - SPAN OVER TO 6.0 METER ----- 21 DAYS.
2. SPACER BERS:- SHALL BE 20MM DIA AS MAX. 4'-0"(1200) INTERVALS

DESIGN DATA:-

GRADE OF CONCRETE SHALL BE M-25.
GRADE OF STEEL SHALL BE Fe-550 D (Primary Producers Only)

DESIGN FOR :-


BUILDING DESIGN FOR B+S+G+5
SBC = 12 MT/Sq.M@3.0M

PROJECT:	PROPOSED RESIDENTIAL BUILDING ON PLOT NO. - 45 SCHEME -24 (RAJAT VIHAR), JAIPUR		
DRAWING TITLE:	RAFT TOP PEDESTAL LAYOUT		
ARCHITECTS:	4 INSIDE ARCHITECTURE N INTERIORS Plot no. 72, S.P. Marg, C- Scheme jaipur, rajasthan, India cont: +91 9950595991, 91 9982812777 e-mail: jeets.arch@gmail.com		
DRAWN BY:	SUNNY	DRAWING. NO.	SDC-4IN-MPR45-03
CHECKED BY:	RAHUL	REVISION NO.	R-00
SCALE:	N.T.S.	DATE:	JUNE.14/2024


STRUCTURAL CONSULTANT:





SHYAM DESIGN CONSULTANTS
ER. RAHULSHARMA (M.Tech Str.)
M: 9680459482, 9929039105
Email: shyamdesignconsultants1211@gmail.com



RAFT BOTTOM EXTRA R/f PLAN (PARALLEL TO X-DIRECTION)



RAFT BOTTOM EXTRA R/f PLAN (PARALLEL TO Y-DIRECTION)



PROJECT NAME:-
THE ROYALS PALACE

DEVELOPER NAME :-
SHREE RAM INFRA

- GENERAL NOTES:-
1. ALL DIMENSION AND LEVEL ARE IN FEET & INCHES.
 2. DO NOT SCALE THIS DRAWING. FOLLOW WRITTEN DIMENSION ONLY.
 3. THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVANT ARCHITECTURAL AND SERVICE DRAWING. ANY DISCREPANCY SHOULD BE IMMEDIATELY BROUGHT TO NOTICE.
 4. ONLY LOAD BEARING WALLS ARE SHOWN IN PLAN. OTHER WALLS SHALL BE STOPPED 1/2" BELOW SOFFIT OF BEAM/SLAB AND GAP FILLED WITH LEAN CEMENT MORTAR UNLESS OTHERWISE SHOWN IN ARCHITECTURAL DRAWING.

- REINFORCEMENT DETAILS
1. HIGH YIELD STRENGTH DEFORMED BARS MARKED AS Ø WITH CHARACTERISTIC STRENGTH 500 N/MM CONFORMING TO IS 1786-2008 SHALL BE USED.
 2. LAP IN SLAB & BEAMS OF SUPER STRUCTURE CLOSE TO MID SPAN FOR BOTTOM BARS & CLOSE TO SUPPORT FOR TOP BARS SHALL BE AVOIDED.
 3. LAP SHALL BE STAGGERED SO THAT NO MORE THAN 1/2 OF BARS SHALL BE LAPPED AT ANY SECTION.
 4. LAP LENGTH FOR HIGH YIELD STRENGTH DEFORMED BARS SHALL BE AS FOLLOW, WHERE Ø IS DIA. OF BARS.

CONC. GRADE	L _{dt}
M-20	570
M-25	490
M-30	450
M-35	400

5. TIES OR DISTRIBUTION REINFORCEMENT IN THE SLAB SHALL BE PROVIDED OF 80@8"C/C OTHERWISE MENTIONED.

- CONCRETE DETAILS
1. NOMINAL SIZE OF CRUSHED STONE GRADED AGGR-GATE SHALL BE 3/4" UNLESS OTHERWISE STATED.
 2. GRADE OF CONCRETE SHALL BE M-25 CONFORMING TO IS 456-2000 UNLESS OTHERWISE NOTED.
 3. CLEAR COVER OF CONCRETE IN INCHES TO THE MAIN REINFORCEMENT UNLESS SPECIFIED OTHERWISE SHALL BE :-

PARTICULAR	BOTTOM	TOP	SIDES
FOOTING	50mm	50mm	50mm
COLUMNS & WALLS	40mm	40mm	40mm
RETAINING WALL	25mm	40mm (EARTH SIDE)	25mm (ON SLOPE)
BEAMS, LINTEL	25mm	25mm	25mm
SLAB	20mm	15mm	25mm (WHERE APPLICABLE)
WATER TANK (WALL & SLAB)	25mm (ON WATER FACE)	25mm (ON WATER FACE)	40mm (ON EARTH SIDE)


- MISCELLANEOUS
1. REMOVAL OF SHUTTERING - THIS SHALL BE AS UNLESS OTHERWISE STATED.
 - * WALL, COL & VERTICAL FACE OF ALL MEMBERS 24 TO 48 HOURS.
 - * SLABS (PROPS LEFT UNDER) 7 DAYS.
 - * BEAM SOFFITS (PROPS LEFT) 7 DAYS.
 - * REMOVAL OF PROPS UNDER SLAB 7 DAYS.
 - SPAN UP TO 4.5 METER 14 DAYS.
 - SPAN OVER TO 6.0 METER 21 DAYS.
 2. SPACER BERS - SHALL BE 20MM DIA AS MAX. 4'-0"(1200) INTERVALS.

DESIGN DATA:-
GRADE OF CONCRETE SHALL BE M-25.
GRADE OF STEEL SHALL BE Fe-550 D (Primary Producers Only)


DESIGN FOR :-
BUILDING DESIGN FOR B+S+G+5
SBC = 12 MT/Sq.M @ 3.0M

PROJECT:	PROPOSED RESIDENTIAL BUILDING ON PLOT NO. - 45 SCHEME -24 (RAJAT VIHAR), JAIPUR		
DRAWING TITLE:	RAFT BOTTOM EXTRA R/1 PLAN (PARALLEL TO X & Y-DIR) LAYOUT		
ARCHITECTS:	4 th INSIDE ARCHITECTURE N INTERIORS Plot no. 72, S.F. Marg, C- Scheme jaipur, rajasthan, India cont. +91 9930393991, 91 9982812777 e-mail: jee.arch@gmail.com		
DRAWN BY:	SUNNY	DRAWING NO.	SDC-4N-MPR4S-04
CHECKED BY:	RAHUL	REVISION NO.	R-00
SCALE:	N.T.S.	DATE:	JUNE 14/2024







SECTION (1-1)
F-1




SECTION (2-2)
F-2




SECTION (4-4)
F-4




SECTION (X-X)





SECTION (Y-Y)



SECTION (Y-Y)



SECTION (3-3)
F-3



PROJECT NAME:-
THE ROYALS PALACE
DEVELOPER NAME :-
SHREE RAM INFRA

GENERAL NOTES:-

- ALL DIMENSION AND LEVEL ARE IN FEET & INCHES
- DO NOT SCALE THIS DRAWING. FOLLOW WRITTEN DIMENSION ONLY.
- THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVANT ARCHITECTURAL AND SERVICE DRAWING ANY DISCREPANCY SHOULD BE IMMEDIATELY BROUGHT TO NOTICE
- ONLY LOAD BEARING WALLS ARE SHOWN IN PLAN. OTHER WALLS SHALL BE STOPPED 1/2" BELOW SOFFIT OF BEAM/SLAB AND GAP FILLED WITH LEAN CEMENT MORTAR UNLESS OTHERWISE SHOWN IN ARCHITECTURAL DRAWING.

REINFORCEMENT DETAILS

- HIGH YIELD STRENGTH DEFORMED BARS MARKED AS Ø WITH CHARACTERISTIC STRENGTH 500 N/MM CONFORMING TO IS 1786-2008, SHALL BE USED.
- LAP IN SLAB & BEAMS OF SUPER STRUCTURE CLOSE TO MID SPAN FOR BOTTOM BARS & CLOSE TO SUPPORT FOR TOP BARS SHALL BE AVOIDED.
- LAP SHALL BE STAGGERED SO THAT NO MORE THAN 1/2 OF BARS SHALL BE LAPPED AT ANY SECTION
- LAP LENGTH FOR HIGH YIELD STRENGTH DEFORMED BARS SHALL BE AS FOLLOW. WHERE Ø IS DIA OF BARS.

CONC.GRADE	Ldt
M-20	57Ø
M-25	49Ø
M-30	45Ø
M-35	40Ø

- TIES OR DISTRIBUTION REINFORCEMENT IN THE SLAB SHALL BE PROVIDED OF 8Ø@8"C/C OTHERWISE MENTIONED.

CONCRETE DETAILS

- NOMINAL SIZE OF CRUSHED STONE GRADED AGGR-GATE SHALL BE 3/4" UNLESS OTHERWISE STATED.
- GRADE OF CONCRETE SHALL BE M-25 CONFORMING TO IS 456-2000 UNLESS OTHERWISE NOTED.
- CLEAR COVER OF CONCRETE IN INCHES TO THE MAIN REINFORCEMENT UNLESS SPECIFIED OTHERWISE SHALL BE :-

PARTICULAR	BOTTOM	TOP	SIDES
FOOTING	50mm	50mm	50mm
COLUMNS/S WALLS			40mm
RETAINING WALL		25mm	40mm (EARTH SIDE) 20mm (IN SIDE)
BEAMS, LINTEL	25mm	25mm	25mm
SLAB	20mm	15mm	25mm (WHERE APPLICABLE)
WATER TANK (WALL & SLAB)		25mm (ON WATER FACE) 40mm (ON EARTH SIDE)	

MISCELLANEOUS

- REMOVAL OF SHUTTERING:- THIS SHALL BE AS UNLESS OTHERWISE STATED.
 - * WALL, COL & VERTICAL FACE OF ALL MEMBERS 24 TO 48 HOURS.
 - * SLABS (PROPS LEFT UNDER) ----- 3 DAYS.
 - * BEAM SOFFITS (PROPS LEFT) ----- 7 DAYS.
 - * REMOVAL OF PORPS UNDER SLAB ----- 7 DAYS.
 - SPAN UP TO 4.5 METER ----- 14 DAYS.
 - SPAN OVER TO 6.0 METER ----- 21 DAYS.
- SPACER BERS:- SHALL BE 20MM DIA AS MAX. 4'-0"(1200) INTERVALS

DESIGN DATA:-

GRADE OF CONCRETE SHALL BE M-25.
GRADE OF STEEL SHALL BE Fe-550 D (Primary Producers Only)






DESIGN FOR :-

BUILDING DESIGN FOR B+S+G+5
SBC = 12 MT/Sq.M@3.0M

PROJECT:	PROPOSED RESIDENTIAL BUILDING ON PLOT NO. -45 SCHEME -24 (RAJAT VIHAR), JAIPUR		
DRAWING TITLE:	RAFT FOUNDATION SECTIONS		
ARCHITECTS:	4 INSIDE ARCHITECTURE N INTERIORS Plot no. 72, S.P. Marg, C-Scheme jaipur, rajasthan, India cont: +91 9950595991, 91 9982812777 e-mail: jeets.arch@gmail.com		
DRAWN BY:	SUNNY	DRAWING. NO.	SDC-4IN-MPR45-05
CHECKED BY:	RAHUL	REVISION NO.	R-00
SCALE:	N.T.S.	DATE:	JUNE.14/2024

STRUCTURAL CONSULTANT:










RINGS DETAIL

R-1 = #8@4"C/C

R-2 = #8@8"C/C

R-3 = #8@6"C/C



PROJECT NAME:-
THE ROYALS PALACE

DEVELOPER NAME :-
SHREE RAM INFRA

GENERAL NOTES:-

- ALL DIMENSION AND LEVEL ARE IN FEET & INCHES
- DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSION ONLY.
- THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVANT ARCHITECTURAL AND SERVICE DRAWING ANY DISCREPANCY SHOULD BE IMMEDIATELY BROUGHT TO NOTICE.
- ONLY LOAD BEARING WALLS ARE SHOWN IN PLAN OTHER WALLS SHALL BE STOPPED 1/2" BELOW SOFFIT OF BEAM/SLAB AND GAP FILLED WITH LEAN CEMENT MORTAR UNLESS OTHERWISE SHOWN IN ARCHITECTURAL DRAWING.

REINFORCEMENT DETAILS

- HIGH YIELD STRENGTH DEFORMED BARS MARKED AS B WITH CHARACTERISTIC STRENGTH 500 N/MM CONFORMING TO IS 1786-2008, SHALL BE USED.
- LAP IN SLAB & BEAMS OF SUPER STRUCTURE CLOSE TO MID SPAN FOR BOTTOM BARS & CLOSE TO SUPPORT FOR TOP BARS SHALL BE AVOIDED.
- LAP SHALL BE STAGGERED SO THAT NO MORE THAN 1/2 OF BARS SHALL BE LAPPED AT ANY SECTION.
- LAP LENGTH FOR HIGH YIELD STRENGTH DEFORMED BARS SHALL BE AS FOLLOW, WHERE Ø IS DIA OF BARS.

CONC. GRADE	L/D
M-20	57Ø
M-25	48Ø
M-30	45Ø
M-35	40Ø

5. TIES OR DISTRIBUTION REINFORCEMENT IN THE SLAB SHALL BE PROVIDED OF 8Ø@8"C/C OTHERWISE MENTIONED.

CONCRETE DETAILS

- NOMINAL SIZE OF CRUSHED STONE GRADED AGGR-GATE SHALL BE 3/4" UNLESS OTHERWISE STATED.
- GRADE OF CONCRETE SHALL BE M-25 CONFORMING TO IS 456-2000 UNLESS OTHERWISE NOTED.
- CLEAR COVER OF CONCRETE IN INCHES TO THE MAIN REINFORCEMENT UNLESS SPECIFIED OTHERWISE SHALL BE -

PARTICULAR	BOTTOM	TOP	SIDES
FOOTING	50mm	50mm	50mm
COLUMN & WALLS	40mm	40mm	40mm
RETAINING WALL	20mm	20mm	20mm (ON SIDE)
BEAM/ LINTEL	25mm	25mm	25mm
SLAB	20mm	20mm	20mm (ON WATER FACE)
WATER TANK (WALL & SLAB)	25mm	25mm	40mm (ON OTHER SIDE)

MISCELLANEOUS

- REMOVAL OF SHUTTERING:- THIS SHALL BE AS UNLESS OTHERWISE STATED.
* WALL, COL. & VERTICAL FACE OF ALL MEMBERS 24 TO 48 HOURS
* SLABS (PROPS LEFT UNDER) 7 DAYS
* BEAM SOFFITS (PROPS LEFT) 7 DAYS
* REMOVAL OF PROPS UNDER SLAB 7 DAYS
* SPAN OVER TO 4.5 METER 14 DAYS
* SPAN OVER TO 6.0 METER 21 DAYS
- SPACER BERS:- SHALL BE 20MM DIA AS MAX. 4'-0"(1200) INTERVALS

DESIGN DATA:-

GRADE OF CONCRETE SHALL BE M-25.
GRADE OF STEEL SHALL BE Fe-550 D (Primary Producers Only)



DESIGN FOR :-

BUILDING DESIGN FOR B+S+G+5
SBC ~12 MT/Gq M/G/S DM


PROJECT:	PROPOSED RESIDENTIAL BUILDING ON PLOT NO.-48 SCHEME-24 (RAJAT VIHAR), JAIPUR		
DRAWING TITLE:	STAIR CASE DETAILS		
ARCHITECTS:	4 INSIDE ARCHITECTURE N INTERIORS Plot no. 72, S.P. Marg., C-Scheme jaipur, cont:- +91 9920939911, 91 9920812777 e-mail: jeet.ash@gmail.com		
DRAWN BY:	SUNNY	DRAWING NO.	SDC-
CHECKED BY:	RAHUL	REVISION NO.	01-08
SCALE:	N.T.S.	DATE:	JUNE 26/2024

STRUCTURAL CONSULTANT:





2-Legged Ring



TYPICAL CUT OUT
DETAIL



PROJECT NAME:-
THE ROYALS PALACE

DEVELOPER NAME :-
SHREE RAM INFRA

- GENERAL NOTES:-
- ALL DIMENSION AND LEVEL ARE IN FEET & INCHES
 - DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSION ONLY.
 - THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVANT ARCHITECTURAL AND SERVICE DRAWING ANY DISCREPANCY SHOULD BE IMMEDIATELY BROUGHT TO NOTICE.
 - ONLY LOAD BEARING WALLS ARE SHOWN IN PLAN OTHER WALLS SHALL BE STOPPED 1/2" BELOW SOFFIT OF BEAM/SLAB AND GAP FILLED WITH LEAN CEMENT MORTAR UNLESS OTHERWISE SHOWN IN ARCHITECTURAL DRAWING.

- REINFORCEMENT DETAILS
- HIGH YIELD STRENGTH DEFORMED BARS MARKED AS Ø WITH CHARACTERISTIC STRENGTH 500 N/MM CONFORMING TO IS 1786-2008, SHALL BE USED.
 - LAP IN SLAB & BEAMS OF SUPER STRUCTURE CLOSE TO MID SPAN FOR BOTTOM BARS & CLOSE TO SUPPORT FOR TOP BARS SHALL BE AVOIDED.
 - LAP SHALL BE STAGGERED SO THAT NO MORE THAN 1/2 OF BARS SHALL BE LAPPED AT ANY SECTION
 - LAP LENGTH FOR HIGH YIELD STRENGTH DEFORMED BARS SHALL BE AS FOLLOW. WHERE Ø IS DIA OF BARS.

CONC. GRADE	Ldt
M-20	57Ø
M-25	49Ø
M-30	45Ø
M-35	40Ø

- TIES OR DISTRIBUTION REINFORCEMENT IN THE SLAB SHALL BE PROVIDED OF 8Ø@8"C/C OTHERWISE MENTIONED.

- CONCRETE DETAILS
- NOMINAL SIZE OF CRUSHED STONE GRADED AGGR-GATE SHALL BE 3/4" UNLESS OTHERWISE STATED.
 - GRADE OF CONCRETE SHALL BE M-25 CONFORMING TO IS 456-2000 UNLESS OTHERWISE NOTED.
 - CLEAR COVER OF CONCRETE IN INCHES TO THE MAIN REINFORCEMENT UNLESS SPECIFIED OTHERWISE SHALL BE :-

PARTICULAR	BOTTOM	TOP	SIDES
FOOTING	50mm	50mm	50mm
COLUMNS/ S WALLS			40mm
RETAINING WALL		25mm	40mm (EARTH SIDE) 20mm (IN SIDE)
BEAMS, LINTEL	25mm	25mm	25mm
SLAB	20mm	15mm	25mm (WHERE APPLICABLE)
WATER TANK (WALL & SLAB)			25mm (ON WATER FACE) 40mm (ON EARTH SIDE)


- MISCELLANEOUS
- REMOVAL OF SHUTTERING:- THIS SHALL BE AS UNLESS OTHERWISE STATED.
 - * WALL, COL & VERTICAL FACE OF ALL MEMBERS 24 TO 48 HOURS.
 - * SLABS (PROPS LEFT UNDER) ----- 3 DAYS.
 - * BEAM SOFFITS (PROPS LEFT) ----- 7 DAYS.
 - * REMOVAL OF PORPS UNDER SLAB ----- 7 DAYS.
 - SPAN UP TO 4.5 METER ----- 14 DAYS.
 - SPAN OVER TO 6.0 METER ----- 21 DAYS.
 - SPACER BERS:- SHALL BE 20MM DIA AS MAX. 4'-0"(1200) INTERVALS


DESIGN DATA:-
GRADE OF CONCRETE SHALL BE M-25.
GRADE OF STEEL SHALL BE Fe-550 D (Primary Producers Only)

DESIGN FOR :-
BUILDING DESIGN FOR B+S+G+5
SBC =12 MT/Sq.M@3.0M


PROJECT:	PROPOSED RESIDENTIAL BUILDING ON PLOT NO. - 45 SCHEME -24 (RAJAT VIHAR), JAIPUR		
DRAWING TITLE:	BASEMENT ROOF & PLINTH BEAM LAYOUT		
ARCHITECTS:	4 INSIDE ARCHITECTURE N INTERIORS Plot no. 72, S.P. Marg., C- Scheme jaipur, rajasthan, India cont: +91 9950595991, 91 9982812777 e.mail: jeets.arch@gmail.com		
DRAWN BY:	SUNNY	DRAWING. NO.	SDC-4IN-MPR45-07
CHECKED BY:	RAHUL	REVISION NO.	R-00
SCALE:	N.T.S.	DATE:	JUNE.14/2024

STRUCTURAL CONSULTANT:







PB1(12\"X18\")




PB2(12\"X18\")




PB3(12\"X18\")




PB4(12\"X18\")




PB5(12\"X18\")




PB6(12\"X18\")




PB7(12\"X18\")




PB8(12\"X18\")




PB9(12\"X18\")




PB12(12\"X18\")




PB10(12\"X18\")




PB11(12\"X18\")




PB13(12\"X18\")




PB14(12\"X18\")




PB15(12\"X18\")




B1(9\"X18\")




B2(9\"X18\")




B3(9\"X18\")




B4(12\"X18\")




B5/B7(9\"X18\")




FLAT(12\"X6\")




B6(9\"X18\")



B8(9\"X18\")



B9(9\"X18\")



B10(9\"X18\")



PROJECT NAME:-
THE ROYALS PALACE
DEVELOPER NAME :-
SHREE RAM INFRA

GENERAL NOTES:-

- ALL DIMENSION AND LEVEL ARE IN FEET & INCHES
- DO NOT SCALE THIS DRAWING. FOLLOW WRITTEN DIMENSION ONLY.
- THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVANT ARCHITECTURAL AND SERVICE DRAWING ANY DISCREPANCY SHOULD BE IMMEDIATELY BROUGHT TO NOTICE
- ONLY LOAD BEARING WALLS ARE SHOWN IN PLAN. OTHER WALLS SHALL BE STOPPED 1/2\"/>

REINFORCEMENT DETAILS

- HIGH YIELD STRENGTH DEFORMED BARS MARKED AS Ø WITH CHARACTERISTIC STRENGTH 500 N/MM CONFORMING TO IS 1786-2008, SHALL BE USED.
- LAP IN SLAB & BEAMS OF SUPER STRUCTURE CLOSE TO MID SPAN FOR BOTTOM BARS & CLOSE TO SUPPORT FOR TOP BARS SHALL BE AVOIDED.
- LAP SHALL BE STAGGERED SO THAT NO MORE THAN 1/2 OF BARS SHALL BE LAPPED AT ANY SECTION
- LAP LENGTH FOR HIGH YIELD STRENGTH DEFORMED BARS SHALL BE AS FOLLOW. WHERE Ø IS DIA OF BARS.

CONC.GRADE	Ldt
M-20	570
M-25	490
M-30	450
M-35	400

- TIES OR DISTRIBUTION REINFORCEMENT IN THE SLAB SHALL BE PROVIDED OF 80@8\"/>

CONCRETE DETAILS

- NOMINAL SIZE OF CRUSHED STONE GRADED AGGR-GATE SHALL BE 3/4\"/>
- GRADE OF CONCRETE SHALL BE M-25 CONFORMING TO IS 456-2000 UNLESS OTHERWISE NOTED.
- CLEAR COVER OF CONCRETE IN INCHES TO THE MAIN REINFORCEMENT UNLESS SPECIFIED OTHERWISE SHALL BE :-

PARTICULAR	BOTTOM	TOP	SIDES
FOOTING	50mm	50mm	50mm
COLUMNS/S WALLS			40mm
RETAINING WALL		25mm	40mm (EARTH SIDE) 20mm (IN SIDE)
BEAMS, LINTEL	25mm	25mm	25mm
SLAB	20mm	15mm	25mm (WHERE APPLICABLE)
WATER TANK (WALL & SLAB)			25mm (ON WATER FACE) 40mm (ON ERTH SIDE)

MISCELLANEOUS

- REMOVAL OF SHUTTERING:- THIS SHALL BE AS UNLESS OTHERWISE STATED.
 - * WALL, COL & VERTICAL FACE OF ALL MEMBERS 24 TO 48 HOURS.
 - * SLABS (PROPS LEFT UNDER) ----- 3 DAYS.
 - * BEAM SOFFITS (PROPS LEFT) ----- 7 DAYS.
 - * REMOVAL OF PORPS UNDER SLAB ----- 7 DAYS.
 - SPAN UP TO 4.5 METER ----- 14 DAYS.
 - SPAN OVER TO 6.0 METER ----- 21 DAYS.
- SPACER BERS:- SHALL BE 20MM DIA AS MAX. 4-0\"/>

DESIGN DATA:-

GRADE OF CONCRETE SHALL BE M-25.
GRADE OF STEEL SHALL BE Fe-550 D (Primary Producers Only)

DESIGN FOR :-



BUILDING DESIGN FOR B+S+G+5
SBC =12 MT/Sq.M@3.0M

PROJECT:	PROPOSED RESIDENTIAL BUILDING ON PLOT NO. -45 SCHEME -24 (RAJAT VIHAR), JAIPUR.		
DRAWING TITLE:	BASEMENT ROOF & PLINTH BEAM DETAILS		
ARCHITECTS:	4 INSIDE ARCHITECTURE N INTERIORS Plot no. 72, S.P. Marg, C-Scheme jaipur, rajasthan, India cont: +91 9950595991, 91 9982812777 e-mail: jeets.arch@gmail.com		
DRAWN BY:	SUNNY	DRAWING. NO.	SDC-4IN-MPR45-08
CHECKED BY:	RAHUL	REVISION NO.	R-00
SCALE:	N.T.S.	DATE:	JUNE.14/2024

STRUCTURAL CONSULTANT:-



SLAB R/F SPECIFICATIONS :-



GENERAL NOTES:-

- ALL DIMENSION AND LEVEL ARE IN FEET & INCHES.
- DO NOT SCALE THIS DRAWING. FOLLOW WRITTEN DIMENSION ONLY.
- THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVANT ARCHITECTURAL AND SERVICE DRAWING ANY DISCREPANCY SHOULD BE IMMEDIATELY BROUGHT TO NOTICE.
- ONLY LOAD BEARING WALLS ARE SHOWN IN PLAN. OTHER WALLS SHALL BE STOPPED 1/2" BELOW SOFFIT OF BEAM/SLAB AND GAP FILLED WITH LEAN CEMENT MORTAR UNLESS OTHERWISE SHOWN IN ARCHITECTURAL DRAWING.

REINFORCEMENT DETAILS

- HIGH YIELD STRENGTH DEFORMED BARS MARKED AS Ø WITH CHARACTERISTIC STRENGTH 500 N/MM CONFORMING TO IS 1786-2008, SHALL BE USED.
- LAP IN SLAB & BEAMS OF SUPER STRUCTURE CLOSE TO MID SPAN FOR BOTTOM BARS & CLOSE TO SUPPORT FOR TOP BARS SHALL BE AVOIDED.
- LAP SHALL BE STAGGERED SO THAT NO MORE THAN 1/2 OF BARS SHALL BE LAPPED AT ANY SECTION.
- LAP LENGTH FOR HIGH YIELD STRENGTH DEFORMED BARS SHALL BE AS FOLLOW, WHERE Ø IS DIA. OF BARS.

CONC. GRADE	Ldt
M-20	57Ø
M-25	49Ø
M-30	45Ø
M-35	40Ø

- TIES OR DISTRIBUTION REINFORCEMENT IN THE SLAB SHALL BE PROVIDED OF 8Ø@8"C/C OTHERWISE MENTIONED.

CONCRETE DETAILS

- NOMINAL SIZE OF CRUSHED STONE GRADED AGGR-GATE SHALL BE 3/4" UNLESS OTHERWISE STATED.
- GRADE OF CONCRETE SHALL BE M-25 CONFORMING TO IS 456-2000 UNLESS OTHERWISE NOTED.
- CLEAR COVER OF CONCRETE IN INCHES TO THE MAIN REINFORCEMENT UNLESS SPECIFIED OTHERWISE SHALL BE :-

PARTICULAR	BOTTOM	TOP	SIDES
FOOTING	50mm	50mm	50mm
COLUMNS/ S WALLS			40mm
RETAINING WALL		25mm	40mm (EARTH SIDE) 20mm (IN SIDE)
BEAMS, LINTEL	25mm	25mm	25mm
SLAB	20mm	15mm	25mm (WHERE APPLICABLE)
WATER TANK (WALL & SLAB)			25mm (ON WATER FACE) 40mm (ON EARTH SIDE)

MISCELLANEOUS

- REMOVAL OF SHUTTERING:- THIS SHALL BE AS UNLESS OTHERWISE STATED.
* WALL, COL & VERTICAL FACE OF ALL MEMBERS 24 TO 48 HOURS.
* SLABS (PROPS LEFT UNDER) ----- 3 DAYS.
* BEAM SOFFITS (PROPS LEFT) ----- 7 DAYS.
* REMOVAL OF PROPS UNDER SLAB ----- 7 DAYS.
SPAN UP TO 4.5 METER ----- 14 DAYS.
SPAN OVER TO 6.0 METER ----- 21 DAYS.
- SPACER BERS:- SHALL BE 20MM DIA AS MAX. 4'-0"(1200) INTERVALS

DESIGN DATA:-

GRADE OF CONCRETE SHALL BE M-25.
GRADE OF STEEL SHALL BE Fe-550 D (Primary Producers Only)

DESIGN FOR :-

BUILDING DESIGN FOR B+S+G+5
SBC = 12 MT/Sq. M/@3.0M



PROJECT:	PROPOSED RESIDENTIAL BUILDING ON PLOT NO. - 45 SCHEME - 24 (RAJAT VIHAR), JAIPUR.		
DRAWING TITLE:	STILT FLOOR ROOF LAYOUT		
ARCHITECTS:	4 INSIDE ARCHITECTURE N INTERIORS Plot no. 72, S.P. Marg, C-Scheme jaipur, rajasthan, India cont: +91 995095991, 91 9982812777 e-mail: jeets.arch@gmail.com		
DRAWN BY:	SUNNY	DRAWING NO.	SDC-4IN-MP845-09
CHECKED BY:	RAHUL	REVISION NO.	R-00
SCALE:	N.T.S.	DATE:	JULY 07/2024

STRUCTURAL CONSULTANT:




PROJECT NAME:-
THE ROYALS PALACE


DEVELOPER NAME :-
SHREE RAM INFRA



6-Legged Ring



2-Legged Ring



GENERAL NOTES:-

- ALL DIMENSION AND LEVEL ARE IN FEET & INCHES
- DO NOT SCALE THIS DRAWING. FOLLOW WRITTEN DIMENSION ONLY.
- THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVANT ARCHITECTURAL AND SERVICE DRAWING ANY DISCREPANCY SHOULD BE IMMEDIATELY BROUGHT TO NOTICE
- ONLY LOAD BEARING WALLS ARE SHOWN IN PLAN. OTHER WALLS SHALL BE STOPPED 1/2" BELOW SOFFIT OF BEAM/SLAB AND GAP FILLED WITH LEAN CEMENT MORTAR UNLESS OTHERWISE SHOWN IN ARCHITECTURAL DRAWING.

REINFORCEMENT DETAILS

- HIGH YIELD STRENGTH DEFORMED BARS MARKED AS Ø WITH CHARACTERISTIC STRENGTH 500 N/MM CONFORMING TO IS 1786-2008, SHALL BE USED.
- LAP IN SLAB & BEAMS OF SUPER STRUCTURE CLOSE TO MID SPAN FOR BOTTOM BARS & CLOSE TO SUPPORT FOR TOP BARS SHALL BE AVOIDED.
- LAP SHALL BE STAGGERED SO THAT NO MORE THAN 1/2 OF BARS SHALL BE LAPPED AT ANY SECTION
- LAP LENGTH FOR HIGH YIELD STRENGTH DEFORMED BARS SHALL BE AS FOLLOW. WHERE Ø IS DIA OF BARS.

CONC.GRADE	Ldt
M-20	570
M-25	490
M-30	450
M-35	400

- TIES OR DISTRIBUTION REINFORCEMENT IN THE SLAB SHALL BE PROVIDED OF 80@8"C/C OTHERWISE MENTIONED.

CONCRETE DETAILS

- NOMINAL SIZE OF CRUSHED STONE GRADED AGGR-GATE SHALL BE 3/4" UNLESS OTHERWISE STATED.
- GRADE OF CONCRETE SHALL BE M-25 CONFORMING TO IS 456-2000 UNLESS OTHERWISE NOTED.
- CLEAR COVER OF CONCRETE IN INCHES TO THE MAIN REINFORCEMENT UNLESS SPECIFIED OTHERWISE SHALL BE :-

PARTICULAR	BOTTOM	TOP	SIDES
FOOTING	50mm	50mm	50mm
COLUMNS/S WALLS			40mm
RETAINING WALL		25mm	40mm (EARTH SIDE) 20mm (IN SIDE)
BEAMS, LINTEL	25mm	25mm	25mm
SLAB	20mm	15mm	25mm (WHERE APPLICABLE)
WATER TANK (WALL & SLAB)		25mm (ON WATER FACE) 40mm (ON EARTH SIDE)	

MISCELLANEOUS

- REMOVAL OF SHUTTERING:- THIS SHALL BE AS UNLESS OTHERWISE STATED.
 - * WALL, COL & VERTICAL FACE OF ALL MEMBERS 24 TO 48 HOURS.
 - * SLABS (PROPS LEFT UNDER) ----- 3 DAYS.
 - * BEAM SOFFITS (PROPS LEFT) ----- 7 DAYS.
 - * REMOVAL OF PORPS UNDER SLAB ----- 7 DAYS.
 - SPAN UP TO 4.5 METER ----- 14 DAYS.
 - SPAN OVER TO 6.0 METER ----- 21 DAYS.
- SPACER BERS:- SHALL BE 20MM DIA AS MAX. 4'-0"(1200) INTERVALS

DESIGN DATA:-

GRADE OF CONCRETE SHALL BE M-25.
GRADE OF STEEL SHALL BE Fe-550 D (Primary Producers Only)

DESIGN FOR :-





BUILDING DESIGN FOR B+S+G+5
SBC = 12 MT/Sq.M@3.0M

PROJECT:	PROPOSED RESIDENTIAL BUILDING ON PLOT NO. - 45 SCHEME - 24 (RAJAT VIHAR), JAIPUR.		
DRAWING TITLE:	STILT FLOOR ROOF DETAILS		
ARCHITECTS:	4 INSIDE ARCHITECTURE N INTERIORS Plot no. 72, S.P. Marg, C- Scheme jaipur, rajasthan, India cont: +91 9950595991, 91 9982812777 e-mail: jeets.arch@gmail.com		
DRAWN BY:	SUNNY	DRAWING. NO.	SDC-4IN-MPR45-10
CHECKED BY:	RAHUL	REVISION NO.	R-00
SCALE:	N.T.S.	DATE:	JULY 07/2024


STRUCTURAL CONSULTANT:





PROJECT NAME:-
THE ROYALS PALACE
DEVELOPER NAME :-
SHREE RAM INFRA



BEAMS RING SPECIFICATIONS :-



SLAB R/F SPECIFICATIONS :-



PROJECT NAME:-
THE ROYALS PALACE

DEVELOPER NAME :-
SHREE RAM INFRA

GENERAL NOTES:-

- ALL DIMENSION AND LEVEL ARE IN FEET & INCHES
- DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSION ONLY.
- THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVANT ARCHITECTURAL AND SERVICE DRAWING ANY DISCREPANCY SHOULD BE IMMEDIATELY BROUGHT TO NOTICE.
- ONLY LOAD BEARING WALLS ARE SHOWN IN PLAN OTHER WALLS SHALL BE STOPPED 1/2" BELOW SOFFIT OF BEAM/SLAB AND GAP FILLED WITH LEAN CEMENT MORTAR UNLESS OTHERWISE SHOWN IN ARCHITECTURAL DRAWING.

REINFORCEMENT DETAILS

- HIGH YIELD STRENGTH DEFORMED BARS MARKED AS Ø WITH CHARACTERISTIC STRENGTH 500 N/MM CONFORMING TO IS 1786-2008, SHALL BE USED.
- LAP IN SLAB & BEAMS OF SUPER STRUCTURE CLOSE TO MID SPAN FOR BOTTOM BARS & CLOSE TO SUPPORT FOR TOP BARS SHALL BE AVOIDED.
- LAP SHALL BE STAGGERED SO THAT NO MORE THAN 1/2 OF BARS SHALL BE LAPPED AT ANY SECTION.
- LAP LENGTH FOR HIGH YIELD STRENGTH DEFORMED BARS SHALL BE AS FOLLOW, WHERE Ø IS DIA OF BARS.

CONC. GRADE	Ldt
M-20	570
M-25	490
M-30	450
M-35	400

- TIES OR DISTRIBUTION REINFORCEMENT IN THE SLAB SHALL BE PROVIDED OF 8Ø@Ø/C/C OTHERWISE MENTIONED.

CONCRETE DETAILS

- NOMINAL SIZE OF CRUSHED STONE GRADED AGGR-GATE SHALL BE 3/4" UNLESS OTHERWISE STATED.
- GRADE OF CONCRETE SHALL BE M-25 CONFORMING TO IS 456-2000 UNLESS OTHERWISE NOTED.
- CLEAR COVER OF CONCRETE IN INCHES TO THE MAIN REINFORCEMENT UNLESS SPECIFIED OTHERWISE SHALL BE :-

PARTICULAR	BOTTOM	TOP	SIDES
FOOTING	50mm	50mm	50mm
COLUMNS/S WALLS			40mm
RETAINING WALL		25mm	40mm (EARTH SIDE) 20mm (IN SIDE)
BEAMS, LINTEL	25mm	25mm	25mm
SLAB	20mm	15mm	25mm (WHERE APPLICABLE)
WATER TANK (WALL & SLAB)			25mm (ON WATER FACE) 40mm (ON EARTH SIDE)

MISCELLANEOUS

- REMOVAL OF SHUTTERING:- THIS SHALL BE AS UNLESS OTHERWISE STATED.
* WALL, COL & VERTICAL FACE OF ALL MEMBERS 24 TO 48 HOURS.
* SLABS (PROPS LEFT UNDER) ----- 3 DAYS.
* BEAM SOFFITS (PROPS LEFT) ----- 7 DAYS.
* REMOVAL OF PROPS UNDER SLAB ----- 7 DAYS.
SPAN UP TO 4.5 METER ----- 14 DAYS.
SPAN OVER TO 6.0 METER ----- 21 DAYS.
- SPACER BERS:- SHALL BE 20MM DIA AS MAX. 4"-(1200) INTERVALS

DESIGN DATA:-

GRADE OF CONCRETE SHALL BE M-25.
GRADE OF STEEL SHALL BE Fe-550 D (Primary Producers Only)

DESIGN FOR :-

BUILDING DESIGN FOR B+S+G+5
SBC = 12 MT/Sq.M/@3.0M

PROJECT:	PROPOSED RESIDENTIAL BUILDING ON PLOT NO. - 45 SCHEME -24 (RAJAT VIHAR), JAIPUR.		
DRAWING TITLE:	GROUND TO 5th FLOOR ROOF LAYOUT		
ARCHITECTS:	4 INSIDE ARCHITECTURE N INTERIORS Plot no. 72, S.P. Marg., C- Scheme jaipur, rajasthan, India cont: +91 9950595991, 91 9982812777 e.mail: jeets.arch@gmail.com		
DRAWN BY:	SUNNY	DRAWING NO.	SDC-4IN-MPR45-11
CHECKED BY:	RAHUL	REVISION NO.	R-00
SCALE:	N.T.S.	DATE:	AUG 09/2024

STRUCTURAL CONSULTANT:





GENERAL NOTES:-

1. ALL DIMENSION AND LEVEL ARE IN FEET & INCHES
2. DO NOT SCALE THIS DRAWING. FOLLOW WRITTEN DIMENSION ONLY.
3. THIS DRAWING SHOULD BE READ IN CONJUNCTION WITH RELEVANT ARCHITECTURAL AND SERVICE DRAWING ANY DISCREPANCY SHOULD BE IMMEDIATELY BROUGHT TO NOTICE
4. ONLY LOAD BEARING WALLS ARE SHOWN IN PLAN. OTHER WALLS SHALL BE STOPPED 1/2" BELOW SOFFIT OF BEAM/SLAB AND GAP FILLED WITH LEAN CEMENT MORTAR UNLESS OTHERWISE SHOWN IN ARCHITECTURAL DRAWING.

REINFORCEMENT DETAILS

1. HIGH YIELD STRENGTH DEFORMED BARS MARKED AS Ø WITH CHARACTERISTIC STRENGTH 500 N/MM CONFORMING TO IS 1786-2008, SHALL BE USED.
2. LAP IN SLAB & BEAMS OF SUPER STRUCTURE CLOSE TO MID SPAN FOR BOTTOM BARS & CLOSE TO SUPPORT FOR TOP BARS SHALL BE AVOIDED.
3. LAP SHALL BE STAGGERED SO THAT NO MORE THAN 1/2 OF BARS SHALL BE LAPPED AT ANY SECTION
4. LAP LENGTH FOR HIGH YIELD STRENGTH DEFORMED BARS SHALL BE AS FOLLOW. WHERE Ø IS DIA OF BARS.

CONC.GRADE	Ldt
M-20	570
M-25	490
M-30	450
M-35	400

5. TIES OR DISTRIBUTION REINFORCEMENT IN THE SLAB SHALL BE PROVIDED OF 80@8"C/C OTHERWISE MENTIONED.

CONCRETE DETAILS

1. NOMINAL SIZE OF CRUSHED STONE GRADED AGGR-GATE SHALL BE 3/4" UNLESS OTHERWISE STATED.
2. GRADE OF CONCRETE SHALL BE M-25 CONFORMING TO IS 456-2000 UNLESS OTHERWISE NOTED.
3. CLEAR COVER OF CONCRETE IN INCHES TO THE MAIN REINFORCEMENT UNLESS SPECIFIED OTHERWISE SHALL BE :-

PARTICULAR	BOTTOM	TOP	SIDES
FOOTING	50mm	50mm	50mm
COLUMNS/S WALLS			40mm
RETAINING WALL		25mm	40mm (EARTH SIDE) 20mm (IN SIDE)
BEAMS, LINTEL	25mm	25mm	25mm
SLAB	20mm	15mm	25mm (WHERE APPLICABLE)
WATER TANK (WALL & SLAB)		25mm (ON WATER FACE) 40mm (ON EARTH SIDE)	

MISCELLANEOUS

1. REMOVAL OF SHUTTERING:- THIS SHALL BE AS UNLESS OTHERWISE STATED.
 - * WALL, COL & VERTICAL FACE OF ALL MEMBERS 24 TO 48 HOURS.
 - * SLABS (PROPS LEFT UNDER) ----- 3 DAYS.
 - * BEAM SOFFITS (PROPS LEFT) ----- 7 DAYS.
 - * REMOVAL OF PORPS UNDER SLAB ----- 7 DAYS.
 - SPAN UP TO 4.5 METER ----- 14 DAYS.
 - SPAN OVER TO 6.0 METER ----- 21 DAYS.
2. SPACER BERS:- SHALL BE 20MM DIA AS MAX. 4'-0"(1200) INTERVALS

DESIGN DATA:-

GRADE OF CONCRETE SHALL BE M-25.
GRADE OF STEEL SHALL BE Fe-550 D (Primary Producers Only)

DESIGN FOR :-

BUILDING DESIGN FOR B+S+G+5
SBC =12 MT/Sq.M@3.0M

PROJECT:	PROPOSED RESIDENTIAL BUILDING ON PLOT NO. -45 SCHEME -24 (RAJAT VIHAR), JAIPUR.		
DRAWING TITLE:	Ground to 5TH FLOOR ROOF DETAILS		
ARCHITECTS:	4 INSIDE ARCHITECTURE N INTERIORS Plot no. 72, S.P. Marg, C- Scheme jaipur, rajasthan, India cont: +91 9950595991, 91 9982812777 e.mail: jeets.arch@gmail.com		
DRAWN BY:	SUNNY	DRAWING. NO.	SDC-4IN-MPR45-12
CHECKED BY:	RAHUL	REVISION NO.	R-00
SCALE:	N.T.S.	DATE:	AUG 09/2024

STRUCTURAL CONSULTANT:-



PROJECT NAME:-
THE ROYALS PALACE

DEVELOPER NAME :-
SHREE RAM INFRA