




For Parth Sarthi Build Estate (P) Ltd.

Director

Er. Hemant Kachhwaha

M.Tech(Str) B.E.(Civil)

For S.K. CREATIONS

Proprietor/Manager

GRADE OF CONCRETE M-25
GRADE OF STEEL FE - 550D

STRUCTURE CONSULTANT

S.K. CREATIONS

67, GAYTRI NAGAR-A, DURGAPURA, JAIPUR

(RAJASTHAN) 302018

Email -skcreations.hk@gmail.com

MO. +91-9351388735

ARCHITECTS

FRANK SQUARE

ARCHITECTURE | PLANNER | DESIGNER

C-49 VIDYA APARTMENT PARAS MARG,

BAPU NAGAR JAIPUR, (RAJ.)

Email-afranksquare@gmail.com

Mobile-9461302542

GENERAL NOTES :-

- (1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- (2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- (3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-

- (1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- (2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE TO EARTHQUAKES.
- (3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-

- P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
- P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL, SAND WITHOUT GRAVEL AND PEBBLES.
- P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES.
- P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
- P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS
- | | |
|--|----------------|
| * WALLS, COLUMNS AND VERTICAL FACES OF ALL MEMBERS | 36 TO 48 HOURS |
| * SLABS (PROPS LEFT UNDER) | 3 DAYS |
| * BEAM SOFFITS (PROPS LEFT UNDER) | 7 DAYS |
| * REMOVAL OF PROPS UNDER SLABS | |
| -SPANNING UP TO 4500 | 7 DAYS |
| -SPANNING OVER 4500 | 14 DAYS |
| * REMOVAL OF PROPS UNDER BEAMS | |
| -SPANNING UP TO 6000 | 14 DAYS |
| -SPANNING OVER 6000 | 21 DAYS |

CONCRETE :-

- C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
- C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
- C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ldt-550	Ldc-550	Ldt-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-

- R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786-2008.
- R2. REFER TO HIGH YIELD STRENGTH DEFORMED BARS WITH CHARACTERSTIC STRENGTH OF 550D N/mm².
- R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

DESIGN DATA :-

- (1). GRADE OF CONCRETE SHALL BE-
- | | |
|--------------|----------------|
| * FOUNDATION | -M-25 |
| * COLUMNS | - AS/SCHEDULES |
| * ROOF | - M-25 |
- (2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS

NO.	DATE	ISSUED TO	CKD.


PROJECT

PROPOSED BUILDING AT PLOT NO. F-28, F-29 & F-30, 6-D ENGINEERS COLONY, JAIPUR

DRAWING TITLE

FOUNDATION COLUMN MARKING PLAN

DRAWN BY:	DEEPAK
CHECKED BY:	HEMANT KACHHWAHA
DATE:	10.01.2025
REMARK:	



For Parth Sarthi Build Estate (P) Ltd.

Director

Er. Hemant Kachhwaha

M.Tech(Str) B.E.(Civil)

For S.K. CREATIONS

Proprietor/Manager

GRADE OF CONCRETE M-25
GRADE OF STEEL FE - 550D

STRUCTURE CONSULTANT

S.K. CREATIONS

67, GAYTRI NAGAR-A, DURGAPURA,JAIPUR

(RAJASTHAN) 302018

Email -skcreations.hk@gmail.com

MO. +91-9351388735

ARCHITECTS

FRANK SQUARE

ARCHITECTURE | PLANNER | DESIGNER

C-49 VIDYA APARTMENT PARAS MARG,

BAPU NAGAR JAIPUR, (RAJ.)

Email-afranksquare@gmail.com

Mobile-9461302542

GENERAL NOTES :-

- (1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- (2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- (3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-

- (1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- (2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE DUE TO EARTHQUAKES.
- (3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-

- P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
- P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL,SAND WITHOUT GRAVEL AND PEBBLES.
- P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES
- P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
- P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS
- | | |
|--|----------------|
| * WALLS, COLUMNS AND VERTICAL FACES OF ALL MEMBERS | 36 TO 48 HOURS |
| * SLABS (PROPS LEFT UNDER) | 3 DAYS |
| * BEAM SOFFITS (PROPS LEFT UNDER) | 7 DAYS |
| * REMOVAL OF PROPS UNDER SLABS | |
| -SPANNING UP TO 4500 | 7 DAYS |
| -SPANNING OVER 4500 | 14 DAYS |
| * REMOVAL OF PROPS UNDER BEAMS | |
| -SPANNING UP TO 6000 | 14 DAYS |
| -SPANNING OVER 6000 | 21 DAYS |

CONCRETE :-

- C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
- C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
- C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ldt-550	Ldc-550	Ldt-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-

- R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786-2008.
- R2. REFER TO HIGH YEILD STRENGTH DEFORMED BARS WITH CHARACTERSTIC STRENGTH OF 550D N/mm².
- R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

DESIGN DATA :-

- (1). GRADE OF CONCRETE SHALL BE-
- * FOUNDATION -M-25
 - * COLUMNS - AS/SCHEDULES
 - * ROOF - M-25
- (2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS

NO.	DATE	ISSUED TO	CKD.


PROJECT

PROPOSED BUILDING AT PLOT NO. F-28, F-29 & F-30, 6-D ENGINEERS COLONY , JAIPUR

DRAWING TITLE

FOUNDATION LAYOUT PLAN

DRAWN BY:	DEEPAK
CHECKED BY:	HEMANT KACHHWAHA
DATE:	10.01.2025
REMARK:	



For Parth Sarthi Build Estate (P) Ltd.
मेधा 12/17
Director

Er. Hemant Kachhwaha
M.Tech(Str) B.E.(Civil)

For S. K. CREATIONS
Proprietor/Manager

GRADE OF CONCRETE M-25
GRADE OF STEEL FE - 550D

STRUCTURE CONSULTANT

S.K. CREATIONS

67, GAYTRI NAGAR-A, DURGAPURA, JAIPUR

(RAJASTHAN) 302018

Email -skcreations.hk@gmail.com

MO. +91-9351388735

ARCHITECTS

FRANK SQUARE

ARCHITECTURE | PLANNER | DESIGNER

C-49 VIDYA APARTMENT PARAS MARG,

BAPU NAGAR JAIPUR, (RAJ.)

Email-afranksquare@gmail.com

Mobile-9461302542

GENERAL NOTES :-

- (1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- (2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- (3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-

- (1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- (2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE DUE TO EARTHQUAKES.
- (3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-

- P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
 - P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL, SAND WITHOUT GRAVEL AND PEBBLES.
 - P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES.
 - P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
 - P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS
- | | |
|--|----------------|
| * WALLS, COLUMNS AND VERTICAL FACES OF ALL MEMBERS | 36 TO 48 HOURS |
| * SLABS (PROPS LEFT UNDER) | 3 DAYS |
| * BEAM SOFFITS (PROPS LEFT UNDER) | 7 DAYS |
| * REMOVAL OF PROPS UNDER SLABS | |
| -SPANNING UP TO 4500 | 7 DAYS |
| -SPANNING OVER 4500 | 14 DAYS |
| * REMOVAL OF PROPS UNDER BEAMS | |
| -SPANNING UP TO 6000 | 14 DAYS |
| -SPANNING OVER 6000 | 21 DAYS |

CONCRETE :-

- C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
- C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
- C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ldt-550	Ldc-550	Ldt-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-

- R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786-2008.
 - R2. REFER TO HIGH YIELD STRENGTH DEFORMED BARS WITH CHARACTERSTIC STRENGTH OF 550D N/mm².
 - R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

DESIGN DATA :-

- (1). GRADE OF CONCRETE SHALL BE-
 - * FOUNDATION -M-25
 - * COLUMNS - AS/SCHEDULES
 - * ROOF - M-25
- (2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS


NO.	DATE	ISSUED TO	CKD.

PROJECT
PROPOSED BUILDING AT PLOT NO. F-28,
F-29 & F-30, 6-D ENGINEERS COLONY ,
JAIPUR


DRAWING TITLE

FOUNDATION BOTTOM
EXTRA PLAN

DRAWN BY:	DEEPAK
CHECKED BY:	HEMANT KACHHWAHA
DATE:	10.01.2025
REMARK:	



RAFT SECTION - 1-1



RAFT SECTION - 2-2

For Parth Sarthi Build Estate (P) Ltd.
Signature
Director

Er. Hemant Kachhwaha
M.Tech(Str) B.E.(Civil)
Signature
Proprietor/Manager

GRADE OF CONCRETE M-25
GRADE OF STEEL FE - 550D

STRUCTURE CONSULTANT

S.K. CREATIONS

67, GAYTRI NAGAR-A, DURGAPURA,JAIPUR
(RAJASTHAN) 302018
Email -skcreations.hk@gmail.com
MO. +91-9351388735

ARCHITECTS

FRANK SQUARE

ARCHITECTURE | PLANNER | DESIGNER
C-49 VIDYA APARTMENT PARAS MARG,
BAPU NAGAR JAIPUR, (RAJ.)
Email-afranksquare@gmail.com
Mobile-9461302542

GENERAL NOTES :-

- (1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- (2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- (3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-

- (1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- (2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE DUE TO EARTHQUAKES.
- (3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-

- P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
- P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL,SAND WITHOUT GRAVEL AND PEBBLES.
- P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES
- P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
- P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS
- | | |
|-----------------------------------|----------------|
| * WALLS, COLUMNS AND VERTICAL | |
| FACES OF ALL MEMBERS | 36 TO 48 HOURS |
| * SLABS (PROPS LEFT UNDER) | 3 DAYS |
| * BEAM SOFFITS (PROPS LEFT UNDER) | 7 DAYS |
| * REMOVAL OF PROPS UNDER SLABS | |
| -SPANNING UP TO 4500 | 7 DAYS |
| -SPANNING OVER 4500 | 14 DAYS |
| * REMOVAL OF PROPS UNDER BEAMS | |
| -SPANNING UP TO 6000 | 14 DAYS |
| -SPANNING OVER 6000 | 21 DAYS |

CONCRETE :-

- C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
- C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
- C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ldt-550	Ldc-550	Ldt-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-

- R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786-2008.
- R2. REFER TO HIGH YIELD STRENGTH DEFORMED BARS WITH CHARACTERSTIC STRENGTH OF 550D N/mm².
- R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

DESIGN DATA :-

- (1). GRADE OF CONCRETE SHALL BE-
- * FOUNDATION -M-25
 - * COLUMNS - AS/SCHEDULES
 - * ROOF - M-25
- (2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS

NO.	DATE	ISSUED TO	CKD.

PROJECT

PROPOSED BUILDING AT PLOT NO. F-28, F-29 & F-30, 6-D ENGINEERS COLONY , JAIPUR

DRAWING TITLE

FOUNDATION SECTION DETAIL

DRAWN BY:	DEEPAK
CHECKED BY:	HEMANT KACHHWAHA
DATE:	10.01.2025
REMARK:	

STRUCTURE CONSULTANT

S.K. CREATIONS

67, GAYTRI NAGAR-A, DURGAPURA, JAIPUR

(RAJASTHAN) 302018

Email -skcreations.hk@gmail.com

MO. +91-9351388735

ARCHITECTS

FRANK SQUARE

ARCHITECTURE | PLANNER | DESIGNER
C-49 VIDYA APARTMENT PARAS MARG,
BAPU NAGAR JAIPUR, (RAJ.)
Email-afranksquare@gmail.com
Mobile-9461302542

GENERAL NOTES :-

- (1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- (2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- (3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-

- (1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- (2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE DUE TO EARTHQUAKES.
- (3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-

- P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
- P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL, SAND WITHOUT GRAVEL AND PEBBLES.
- P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES.
- P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
- P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS
- | | |
|--|----------------|
| * WALLS, COLUMNS AND VERTICAL FACES OF ALL MEMBERS | 36 TO 48 HOURS |
| * SLABS (PROPS LEFT UNDER) | 3 DAYS |
| * BEAM SOFFITS (PROPS LEFT UNDER) | 7 DAYS |
| * REMOVAL OF PROPS UNDER SLABS | |
| -SPANNING UP TO 4500 | 7 DAYS |
| -SPANNING OVER 4500 | 14 DAYS |
| * REMOVAL OF PROPS UNDER BEAMS | |
| -SPANNING UP TO 6000 | 14 DAYS |
| -SPANNING OVER 6000 | 21 DAYS |

CONCRETE :-

- C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
- C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
- C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ltd-550	Ldc-550	Ltd-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-

- R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786-2008.
- R2. REFER TO HIGH YIELD STRENGTH DEFORMED BARS WITH CHARACTERSTIC STRENGTH OF 550D N/mm².
- R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

DESIGN DATA :-

- (1). GRADE OF CONCRETE SHALL BE-
- * FOUNDATION -M-25
 - * COLUMNS - AS/SCHEDULES
 - * ROOF - M-25
- (2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS

NO.	DATE	ISSUED TO	CKD.

PROJECT




PROPOSED BUILDING AT PLOT NO. F-28, F-29 & F-30, 6-D ENGINEERS COLONY, JAIPUR

DRAWING TITLE

COLUMN SCHEDULE DETAIL [1]

DRAWN BY:	DEEPAK
CHECKED BY:	HEMANT KACHHWAHA
DATE:	10.01.2025
REMARK:	

COLUMN	C1	C2	C3	C4	C5	C6	C7
FIFTH ROOF TO MUMTY ROOF							
FOURTH ROOF TO FIFTH ROOF	SIZE 9' x 36' MIX. M-25 REINF. 14#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 14#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 14#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C
THIRD ROOF TO FOURTH ROOF	SIZE 9' x 36' MIX. M-25 REINF. 14#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 14#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 14#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 14#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 14#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C
SECOND ROOF TO THIRD ROOF	SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 14#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 14#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C
FIRST ROOF TO SECOND ROOF	SIZE 9' x 36' MIX. M-25 REINF. 14#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#25 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#25 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#25 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#25 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 10#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C
GROUND ROOF TO FIRST ROOF	SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#25 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#25 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#25 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#25 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#25 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C
STILT ROOF TO GROUND ROOF	SIZE 9' x 36' MIX. M-25 REINF. 8#25 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 8#25 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 10#25 4#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 10#25 4#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 10#25 4#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 10#25 4#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 9' x 36' MIX. M-25 REINF. 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C
BASEMENT ROOF TO STILT ROOF	SIZE 12' x 36' MIX. M-25 REINF. 8#25 8#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 12' x 36' MIX. M-25 REINF. 10#25 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 12' x 36' MIX. M-25 REINF. 16#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 12' x 36' MIX. M-25 REINF. 16#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 12' x 36' MIX. M-25 REINF. 16#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 12' x 36' MIX. M-25 REINF. 16#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 12' x 36' MIX. M-25 REINF. 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C
FOUNDATION TO BASEMENT ROOF	SIZE 12' x 36' MIX. M-25 REINF. 8#25 8#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 12' x 36' MIX. M-25 REINF. 10#25 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 12' x 36' MIX. M-25 REINF. 16#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 12' x 36' MIX. M-25 REINF. 16#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 12' x 36' MIX. M-25 REINF. 16#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 12' x 36' MIX. M-25 REINF. 16#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C	SIZE 12' x 36' MIX. M-25 REINF. 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C



For Parth Sarthi Build Estate (P) Ltd.

Director

M.Tech(Str) B.E.(Civil)

S.K. CREATIONS

Proprietor/Manager

GRADE OF CONCRETE M-25
GRADE OF STEEL FE - 550D

- (1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- (2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- (3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-

- (1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- (2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE DUE TO EARTHQUAKES.
- (3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-

- P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
- P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL, SAND WITHOUT GRAVEL AND PEBBLES.
- P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES
- P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
- P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS
- | | |
|--|----------------|
| * WALLS, COLUMNS AND VERTICAL FACES OF ALL MEMBERS | 36 TO 48 HOURS |
| * SLABS (PROPS LEFT UNDER) | 3 DAYS |
| * BEAM SOFFITS (PROPS LEFT UNDER) | 7 DAYS |
| * REMOVAL OF PROPS UNDER SLABS | |
| -SPANNING UP TO 4500 | 7 DAYS |
| -SPANNING OVER 4500 | 14 DAYS |
| * REMOVAL OF PROPS UNDER BEAMS | |
| -SPANNING UP TO 6000 | 14 DAYS |
| -SPANNING OVER 6000 | 21 DAYS |

CONCRETE :-

- C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
- C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
- C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ltd-550	Ldc-550	Ltd-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-

- R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786-2008.
- R2. REFER TO HIGH YIELD STRENGTH DEFORMED BARS WITH CHARACTERSTIC STRENGTH OF 550D N/mm².
- R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

DESIGN DATA :-

- (1). GRADE OF CONCRETE SHALL BE-
 - * FOUNDATION -M-25
 - * COLUMNS - AS/SCHEDULES
 - * ROOF - M-25
- (2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS

NO.	DATE	ISSUED TO	CKD.

PROJECT

PROPOSED BUILDING AT PLOT NO. F-28, F-29 & F-30, 6-D ENGINEERS COLONY, JAIPUR




DRAWING TITLE

COLUMN SCHEDULE DETAIL [2]

DRAWN BY:	DEEPAK
CHECKED BY:	HEMANT KACHHWAHA
DATE:	10.01.2025
REMARK:	

GRADE OF CONCRETE M-25
GRADE OF STEEL FE - 550D

COLUMN	C8				C9				C10				C11				C12				C13				C14							
FIFTH ROOF TO MUMTY ROOF																																
FOURTH ROOF TO FIFTH ROOF	SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'						
	MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25						
	REINF.	14#16			REINF.	8#20			REINF.	8#20			REINF.	8#20			REINF.	8#20			REINF.	8#20			REINF.	8#20						
	RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C						
	RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C						
THIRD ROOF TO FOURTH ROOF	SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'						
	MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25						
	REINF.	8#20			REINF.	14#20			REINF.	14#20			REINF.	14#20			REINF.	14#20			REINF.	14#20			REINF.	14#20						
	RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C						
	RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C						
SECOND ROOF TO THIRD ROOF	SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'						
	MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25						
	REINF.	14#20			REINF.	4#25			REINF.	4#25			REINF.	4#25			REINF.	4#25			REINF.	4#25			REINF.	4#25						
	RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C						
	RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C						
FIRST ROOF TO SECOND ROOF	SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'						
	MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25						
	REINF.	4#25			REINF.	8#25			REINF.	8#25			REINF.	8#25			REINF.	8#25			REINF.	8#25			REINF.	8#25						
	RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C						
	RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C						
GROUND ROOF TO FIRST ROOF	SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'						
	MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25						
	REINF.	8#25			REINF.	8#25			REINF.	8#25			REINF.	8#25			REINF.	8#25			REINF.	8#25			REINF.	8#25						
	RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C						
	RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C						
STILT ROOF TO GROUND ROOF	SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'			SIZE	9' x 36'						
	MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25						
	REINF.	6#20			REINF.	10#25			REINF.	10#25			REINF.	10#25			REINF.	10#25			REINF.	10#25			REINF.	10#25						
	RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C						
	RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C						
BASEMENT ROOF TO STILT ROOF	SIZE	12' x 36'			SIZE	12' x 36'			SIZE	12' x 36'			SIZE	12' x 36'			SIZE	12' x 36'			SIZE	12' x 36'			SIZE	12' x 36'						
	MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25						
	REINF.	10#25			REINF.	16#25			REINF.	16#25			REINF.	16#25			REINF.	16#25			REINF.	16#25			REINF.	16#25						
	RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C						
	RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C						
FOUNDATION TO BASEMENT ROOF	SIZE	12' x 36'			SIZE	12' x 36'			SIZE	12' x 36'			SIZE	12' x 36'			SIZE	12' x 36'			SIZE	12' x 36'			SIZE	12' x 36'						
	MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25			MIX.	M-25						
	REINF.	10#25			REINF.	16#25			REINF.	16#25			REINF.	16#25			REINF.	16#25			REINF.	16#25			REINF.	16#25						
	RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C			RINGS AT SUPPORT	#8@4"C/C						
	RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C			RINGS AT MID SPAN	#8@8"C/C						



For Parth Sarthi Build Estate (P) Ltd.

Director

M.Tech(Str) B.E.(Civil)

S.K. CREATIONS

Proprietor/Manager

- (1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- (2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- (3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-

- (1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- (2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE TO EARTHQUAKES.
- (3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-

- P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
- P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL, SAND WITHOUT GRAVEL AND PEBBLES.
- P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES
- P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
- P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS
- | * WALLS, COLUMNS AND VERTICAL FACES OF ALL MEMBERS | 36 TO 48 HOURS |
|--|----------------|
| * SLABS (PROPS LEFT UNDER) | 3 DAYS |
| * BEAM SOFFITS (PROPS LEFT UNDER) | 7 DAYS |
| * REMOVAL OF PROPS UNDER SLABS | |
| -SPANNING UP TO 4500 | 7 DAYS |
| -SPANNING OVER 4500 | 14 DAYS |
| * REMOVAL OF PROPS UNDER BEAMS | |
| -SPANNING UP TO 6000 | 14 DAYS |
| -SPANNING OVER 6000 | 21 DAYS |

CONCRETE :-

- C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
- C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
- C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ltd-550	Ldc-550	Ltd-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-

- R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786-2008.
- R2. REFER TO HIGH YIELD STRENGTH DEFORMED BARS WITH CHARACTERISTIC STRENGTH OF 5500 N/mm².
- R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

DESIGN DATA :-

- (1). GRADE OF CONCRETE SHALL BE-
 - * FOUNDATION -M-25
 - * COLUMNS - AS/SCHEDULES
 - * ROOF - M-25
- (2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS

NO.	DATE	ISSUED TO	CKD.
-----	------	-----------	------

PROJECT

PROPOSED BUILDING AT PLOT NO. F-28, F-29 & F-30, 6-D ENGINEERS COLONY, JAIPUR

DRAWING TITLE

COLUMN SCHEDULE DETAIL [3]




DRAWN BY: DEEPAK

CHECKED BY: HEMANT KACHHWAHA

DATE: 10.01.2025

REMARK:

COLUMN	C15	C16	C17	C18	C19	C20	C21
FIFTH ROOF TO MUMTY ROOF							
FOURTH ROOF TO FIFTH ROOF	SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#16 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-16# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#16 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-16# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#16 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-16# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20#
THIRD ROOF TO FOURTH ROOF	SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 8#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 6-16# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20#	
SECOND ROOF TO THIRD ROOF	SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20#	SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 4#25 10#20 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 10-20# 4-25# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C 14-20# 8-20# SIZE 9' x 36' MIX. M-25 REINF. 14#20 6#16 RINGS AT SUPPORT #8@4°C/C RINGS AT MID SPAN #8@8°C/C		



For Parth Sarthi Build Estate (P) Ltd.

Director

M.Tech(Str) B.E.(Civil)




S.K. CREATIONS

Proprietor/Manager

GRADE OF CONCRETE M-25
GRADE OF STEEL FE - 550D

GRADE OF CONCRETE M-25
GRADE OF STEEL FE - 550D

COLUMN	C29	C30	C31	C32	C33	C34
FIFTH ROOF TO MUMTY ROOF						
FOURTH ROOF TO FIFTH ROOF	SIZE 9' x 36' MIX. M-25 REINF. 14#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 14-16#	SIZE 9' x 36' MIX. M-25 REINF. 14#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 14-16#	SIZE 9' x 36' MIX. M-25 REINF. 14#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 14-16#	SIZE 9' x 36' MIX. M-25 REINF. 14#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 14-16#	SIZE 9' x 36' MIX. M-25 REINF. 8#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-16#	SIZE 9' x 36' MIX. M-25 REINF. 14#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 14-16#
THIRD ROOF TO FOURTH ROOF	SIZE 9' x 36' MIX. M-25 REINF. 14#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 14-16#	SIZE 9' x 36' MIX. M-25 REINF. 8#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-16#	SIZE 9' x 36' MIX. M-25 REINF. 8#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-16#	SIZE 9' x 36' MIX. M-25 REINF. 14#16 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 14-16#	SIZE 9' x 36' MIX. M-25 REINF. 14#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 14-20#	SIZE 9' x 36' MIX. M-25 REINF. 8#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-16#
SECOND ROOF TO THIRD ROOF	SIZE 9' x 36' MIX. M-25 REINF. 8#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-16#	SIZE 9' x 36' MIX. M-25 REINF. 14#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 14-20#	SIZE 9' x 36' MIX. M-25 REINF. 14#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 14-20#	SIZE 9' x 36' MIX. M-25 REINF. 8#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-16#	SIZE 9' x 36' MIX. M-25 REINF. 4#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 10-20#	SIZE 9' x 36' MIX. M-25 REINF. 14#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 14-20#
FIRST ROOF TO SECOND ROOF	SIZE 9' x 36' MIX. M-25 REINF. 14#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 14-20#	SIZE 9' x 36' MIX. M-25 REINF. 4#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 10-20#	SIZE 9' x 36' MIX. M-25 REINF. 10#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 10-20#	SIZE 9' x 36' MIX. M-25 REINF. 14#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 14-20#	SIZE 9' x 36' MIX. M-25 REINF. 8#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 9' x 36' MIX. M-25 REINF. 10#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 10-20#
GROUND ROOF TO FIRST ROOF	SIZE 9' x 36' MIX. M-25 REINF. 4#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 10-20#	SIZE 9' x 36' MIX. M-25 REINF. 8#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 9' x 36' MIX. M-25 REINF. 4#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 10-20#	SIZE 9' x 36' MIX. M-25 REINF. 10#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 10-20#	SIZE 9' x 36' MIX. M-25 REINF. 8#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 9' x 36' MIX. M-25 REINF. 8#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#
STILT ROOF TO GROUND ROOF	SIZE 9' x 36' MIX. M-25 REINF. 8#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 9' x 36' MIX. M-25 REINF. 8#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 9' x 36' MIX. M-25 REINF. 8#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 9' x 36' MIX. M-25 REINF. 8#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 9' x 36' MIX. M-25 REINF. 10#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 4-20#	SIZE 9' x 36' MIX. M-25 REINF. 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#
BASEMENT ROOF TO STILT ROOF	SIZE 12' x 36' MIX. M-25 REINF. 8#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 12' x 36' MIX. M-25 REINF. 10#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 12' x 36' MIX. M-25 REINF. 10#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 12' x 36' MIX. M-25 REINF. 8#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 12' x 36' MIX. M-25 REINF. 16#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 16-25#	SIZE 12' x 36' MIX. M-25 REINF. 10#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#
FOUNDATION TO BASEMENT ROOF	SIZE 12' x 36' MIX. M-25 REINF. 8#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 12' x 36' MIX. M-25 REINF. 10#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 12' x 36' MIX. M-25 REINF. 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 12' x 36' MIX. M-25 REINF. 8#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#	SIZE 12' x 36' MIX. M-25 REINF. 16#25 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 16-25#	SIZE 12' x 36' MIX. M-25 REINF. 6#20 RINGS AT SUPPORT #8@4"C/C RINGS AT MID SPAN #8@8"C/C 6-20#



For Parth Sarthi Build Estate (P) Ltd.

Director

Er. Hemant Kachhwaha

M.Tech(Str) B.E.(Civil)

S.K. CREATIONS

Proprietor/Manager

GRADE OF CONCRETE M-25
GRADE OF STEEL FE - 550D

STRUCTURE CONSULTANT

S.K. CREATIONS

67, GAYTRI NAGAR-A, DURGAPURA, JAIPUR

(RAJASTHAN) 302018

Email -skcreations.hk@gmail.com

MO. +91-9351388735

ARCHITECTS

FRANK SQUARE

ARCHITECTURE | PLANNER | DESIGNER
C-49 VIDYA APARTMENT PARAS MARG,
BAPU NAGAR JAIPUR, (RAJ.)
Email-afbanksquare@gmail.com
Mobile-9461302542

GENERAL NOTES :-

- (1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- (2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- (3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-

- (1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- (2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE DUE TO EARTHQUAKES.
- (3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-

- P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
 - P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL, SAND WITHOUT GRAVEL AND PEBBLES.
 - P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES
 - P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
 - P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS
- | | |
|--|----------------|
| * WALLS, COLUMNS AND VERTICAL FACES OF ALL MEMBERS | 36 TO 48 HOURS |
| * SLABS (PROPS LEFT UNDER) | 3 DAYS |
| * BEAM SOFFITS (PROPS LEFT UNDER) | 7 DAYS |
| * REMOVAL OF PROPS UNDER SLABS | |
| -SPANNING UP TO 4500 | 7 DAYS |
| -SPANNING OVER 4500 | 14 DAYS |
| * REMOVAL OF PROPS UNDER BEAMS | |
| -SPANNING UP TO 6000 | 14 DAYS |
| -SPANNING OVER 6000 | 21 DAYS |

CONCRETE :-

- C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
- C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
- C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ltd-550	Ldc-550	Ltd-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-

- R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786-2008.
 - R2. REFER TO HIGH YIELD STRENGTH DEFORMED BARS WITH CHARACTERSTIC STRENGTH OF 550D N/mm².
 - R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

DESIGN DATA :-

- (1). GRADE OF CONCRETE SHALL BE-
 - * FOUNDATION -M-25
 - * COLUMNS - AS/SCHEDULES
 - * ROOF - M-25
- (2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS

NO.	DATE	ISSUED TO	CKD.
-----	------	-----------	------

PROJECT

PROPOSED BUILDING AT PLOT NO. F-28, F-29 & F-30, 6-D ENGINEERS COLONY, JAIPUR

DRAWING TITLE

COLUMN SCHEDULE DETAIL [5]

DRAWN BY: DEEPAK

CHECKED BY: HEMANT KACHHWAHA

DATE: 10.01.2025

REMARK:

STRUCTURE CONSULTANT

S.K. CREATIONS

67, GAYTRI NAGAR-A, DURGAPURA, JAIPUR

(RAJASTHAN) 302018

Email -skcreations.hk@gmail.com

MO. +91-9351388735

ARCHITECTS

FRANK SQUARE

ARCHITECTURE | PLANNER | DESIGNER
C-49 VIDYA APARTMENT PARAS MARG,
BAPU NAGAR JAIPUR, (RAJ.)
Email-afranksquare@gmail.com
Mobile-9461302542

GENERAL NOTES :-

- (1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- (2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- (3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-

- (1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- (2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE DUE TO EARTHQUAKES.
- (3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-

- P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
- P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL, SAND WITHOUT GRAVEL AND PEBBLES.
- P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES.
- P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
- P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS
- | | |
|--|----------------|
| * WALLS, COLUMNS AND VERTICAL FACES OF ALL MEMBERS | 36 TO 48 HOURS |
| * SLABS (PROPS LEFT UNDER) | 3 DAYS |
| * BEAM SOFFITS (PROPS LEFT UNDER) | 7 DAYS |
| * REMOVAL OF PROPS UNDER SLABS | |
| -SPANNING UP TO 4500 | 7 DAYS |
| -SPANNING OVER 4500 | 14 DAYS |
| * REMOVAL OF PROPS UNDER BEAMS | |
| -SPANNING UP TO 6000 | 14 DAYS |
| -SPANNING OVER 6000 | 21 DAYS |

CONCRETE :-

- C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
- C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
- C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ldt-550	Ldc-550	Ldt-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-

- R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786-2008.
- R2. REFER TO HIGH YIELD STRENGTH DEFORMED BARS WITH CHARACTERSTIC STRENGTH OF 550D N/mm².
- R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

DESIGN DATA :-

- (1). GRADE OF CONCRETE SHALL BE-
- * FOUNDATION -M-25
 - * COLUMNS - AS/SCHEDULES
 - * ROOF - M-25
- (2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS

NO.	DATE	ISSUED TO	CKD.
-----	------	-----------	------

PROJECT

PROPOSED BUILDING AT PLOT NO. F-28, F-29 & F-30, 6-D ENGINEERS COLONY, JAIPUR

DRAWING TITLE


BASEMENT FLOOR SHUTTERING

DRAWN BY: DEEPAK

CHECKED BY: HEMANT KACHHWAHA

DATE: 27.01.2025

REMARK:



For Parth Sarthi Build Estate (P) Ltd.


Director

Er. Hemant Kachhwaha

M.Tech(Str) B.E.(Civil)

For S.K. CREATIONS

Proprietor/Manager



TYP.BAR CURTAILMENT IN SLAB

GRADE OF CONCRETE M-25
GRADE OF STEEL FE - 550D

R.C.C. SLAB DETAILS:-

SLAB NO.	SHORT SPAN	LONG SPAN	CRANK BAR	THICK	GRADE
S1	#8@5"C/C	#8@5"C/C	#8@7"C/C	0'-6"	M-25
S2	#10@6"C/C	#8@6"C/C	#8@7"C/C	0'-6"	M-25
S3	#10@5"C/C	#10@5"C/C	#8@7"C/C	0'-6"	M-25
S4	#10@4"C/C	#10@6"C/C	#8@7"C/C	0'-6"	M-25

STRUCTURE CONSULTANT

S.K. CREATIONS

67, GAYTRI NAGAR-A, DURGAPURA, JAIPUR

(RAJASTHAN) 302018

Email -skcreations.hk@gmail.com

MO. +91-9351388735

ARCHITECTS

FRANK SQUARE

ARCHITECTURE | PLANNER | DESIGNER

C-49 VIDYA APARTMENT PARAS MARG,

BAPU NAGAR JAIPUR, (RAJ.)

Email-afranksquare@gmail.com

Mobile-9461302542

GENERAL NOTES :-

- (1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- (2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- (3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-

- (1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- (2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE DUE TO EARTHQUAKES.
- (3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-

- P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
- P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL, SAND WITHOUT GRAVEL AND PEBBLES.
- P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES.
- P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
- P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS

* WALLS, COLUMNS AND VERTICAL FACES OF ALL MEMBERS	36 TO 48 HOURS
* SLABS (PROPS LEFT UNDER)	3 DAYS
* BEAM SOFFITS (PROPS LEFT UNDER)	7 DAYS
* REMOVAL OF PROPS UNDER SLABS	
-SPANNING UP TO 4500	7 DAYS
-SPANNING OVER 4500	14 DAYS
* REMOVAL OF PROPS UNDER BEAMS	
-SPANNING UP TO 6000	14 DAYS
-SPANNING OVER 6000	21 DAYS

CONCRETE :-

- C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
- C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
- C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ld-550	Ldc-550	Ld-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-

- R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786-2008.
- R2. REFER TO HIGH YIELD STRENGTH DEFORMED BARS WITH CHARACTERSTIC STRENGTH OF 550D N/mm².
- R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

DESIGN DATA :-

- (1). GRADE OF CONCRETE SHALL BE-
- * FOUNDATION -M-25
 - * COLUMNS - AS/SCHEDULES
 - * ROOF - M-25
- (2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS

NO.	DATE	ISSUED TO	CKD.








PROJECT

PROPOSED BUILDING AT PLOT NO. F-28, F-29 & F-30, 6-D ENGINEERS COLONY , JAIPUR

DRAWING TITLE

BASEMENT ROOF BEAM DETAIL

DRAWN BY:	DEEPAK
CHECKED BY:	HEMANT KACHHWAHA
DATE:	27.01.2025
REMARK:	



For Parth Sarthi Build Estate (P) Ltd.

Director

Er. Hemant Kachhwaha

M.Tech(Str) B.E.(Civil)

S.K. CREATIONS

Proprietor/Manager

S.K. CREATIONS

MO. +91-9351388735

FRANK SQUARE

GENERAL NOTES :-

- 1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- 2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- 3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

- 1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- 2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE DUE TO EARTHQUAKES.
- 3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS:

- | | |
|-----------------------------------|----------------|
| * WALLS, COLUMNS AND VERTICAL | |
| FACES OF ALL MEMBERS | 36 TO 48 HOURS |
| * SLABS (PROPS LEFT UNDER) | 3 DAYS |
| * BEAM SOFFITS (PROPS LEFT UNDER) | 7 DAYS |
| * REMOVAL OF PROPS UNDER SLABS | |
| -SPANNING UP TO 4500 | 7 DAYS |
| -SPANNING OVER 4500 | 14 DAYS |
| * REMOVAL OF PROPS UNDER BEAMS | |
| -SPANNING UP TO 6000 | 14 DAYS |
| -SPANNING OVER 6000 | 21 DAYS |

C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ldt-550	Ldc-550	Ldt-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE

- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

1). GRADE OF CONCRETE SHALL BE-

- * FOUNDATION -M-25
- * COLUMNS - AS/SCHEDULES
- * ROOF - M-25

2). GRADE OF STEEL SHALL BE- FE 550D

NO.	DATE	ISSUED TO	CKD

DATE: 28.01.2025



M.Tech(Str) B.E.(Civil)

For S. K. CREATIONS

Proprietor/Manager



SLAB NO.	SHORT SPAN	LONG SPAN	CRANK BAR	THICK	GRADE
S1	#8@5"C/C	#8@5"C/C	#8@7"C/C	0'-6"	M-25
S2	#8@5"C/C	#8@5"C/C	#8@7"C/C	0'-6"	M-25
S3	#10@6"C/C	#8@6"C/C	#8@7"C/C	0'-6"	M-25
S4	#10@6"C/C	#10@6"C/C	#8@7"C/C	0'-6"	M-25
S5	#10@4"C/C	#10@6"C/C	#8@7"C/C	0'-6"	M-25
S6	#10@4"C/C	#10@4"C/C	#8@7"C/C	0'-6"	M-25

STRUCTURE CONSULTANT

S.K. CREATIONS

67, GAYTRI NAGAR-A, DURGAPURA, JAIPUR

(RAJASTHAN) 302018

Email -skcreations.hk@gmail.com

MO. +91-9351388735

ARCHITECTS

FRANK SQUARE

ARCHITECTURE | PLANNER | DESIGNER

C-49 VIDYA APARTMENT PARAS MARG,

BAPU NAGAR JAIPUR, (RAJ.)

Email-afranksquare@gmail.com

Mobile-9461302542

GENERAL NOTES :-

- (1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- (2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- (3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-

- (1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- (2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE TO EARTHQUAKES.
- (3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-

- P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
 - P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL, SAND WITHOUT GRAVEL AND PEBBLES.
 - P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES.
 - P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
 - P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS
- | | |
|--|----------------|
| * WALLS, COLUMNS AND VERTICAL FACES OF ALL MEMBERS | 36 TO 48 HOURS |
| * SLABS (PROPS LEFT UNDER) | 3 DAYS |
| * BEAM SOFFITS (PROPS LEFT UNDER) | 7 DAYS |
| * REMOVAL OF PROPS UNDER SLABS | |
| -SPANNING UP TO 4500 | 7 DAYS |
| -SPANNING OVER 4500 | 14 DAYS |
| * REMOVAL OF PROPS UNDER BEAMS | |
| -SPANNING UP TO 6000 | 14 DAYS |
| -SPANNING OVER 6000 | 21 DAYS |

CONCRETE :-

- C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
- C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
- C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ldt-550	Ldc-550	Ldt-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-

- R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786:2008.
 - R2. REFER TO HIGH YIELD STRENGTH DEFORMED BARS WITH CHARACTERISTIC STRENGTH OF 550D N/mm².
 - R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

DESIGN DATA :-

- (1). GRADE OF CONCRETE SHALL BE-
 - * FOUNDATION -M-25
 - * COLUMNS - AS/SCHEDULES
 - * ROOF - M-25
- (2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS

NO.	DATE	ISSUED TO	CKD.


PROJECT


PROPOSED BUILDING AT PLOT NO. F-28, F-29 & F-30, 6-D ENGINEERS COLONY, JAIPUR

DRAWING TITLE

STILT FLOOR BEAM DETAIL

DRAWN BY:	DEEPAK
CHECKED BY:	HEMANT KACHHWAHA
DATE:	28.01.2025
REMARK:	





TOP EXTRA
#10@5"C/C

TOP EXTRA
#10@5"C/C

TOP EXTRA
#10@5"C/C

TOP EXTRA
#10@5"C/C

For Parth Sarthi Build Estate (P) Ltd.


Director

Er. Hemant Kachwaha

M.Tech(Str) B.E.(Civil)

For S. K. CREATIONS

Proprietor/Manager



TYP.BAR CURTAILMENT IN SLAB

GRADE OF CONCRETE M-25
GRADE OF STEEL FE - 550D

R.C.C. SLAB DETAILS:-

SLAB NO.	SHORT SPAN	LONG SPAN	CRANK BAR	THICK	GRADE
S1	#8@5"C/C	#8@5"C/C	#8@7"C/C	0'-6"	M-25
S2	#10@6"C/C	#8@6"C/C	#8@7"C/C	0'-6"	M-25
S3	#10@4"C/C	#10@6"C/C	#8@7"C/C	0'-6"	M-25
S4	#10@4"C/C	#10@4"C/C	#8@7"C/C	0'-6"	M-25

STRUCTURE CONSULTANT

S.K. CREATIONS

67, GAYTRI NAGAR-A, DURGAPURA,JAIPUR
(RAJASTHAN) 302018
Email -skcreations.hk@gmail.com
MO. +91-9351388735

ARCHITECTS

FRANK SQUARE

ARCHITECTURE | PLANNER | DESIGNER
C-49 VIDYA APARTMENT PARAS MARG,
BAPU NAGAR JAIPUR, (RAJ.)
Email-afranksquare@gmail.com
Mobile-9461302542

GENERAL NOTES :-

- (1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- (2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- (3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-

- (1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- (2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE DUE TO EARTHQUAKES.
- (3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-

- P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
 - P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL,SAND WITHOUT GRAVEL AND PEBBLES.
 - P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES
 - P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
 - P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS
- | | |
|--|----------------|
| * WALLS, COLUMNS AND VERTICAL FACES OF ALL MEMBERS | 36 TO 48 HOURS |
| * SLABS (PROPS LEFT UNDER) | 3 DAYS |
| * BEAM SOFFITS (PROPS LEFT UNDER) | 7 DAYS |
| * REMOVAL OF PROPS UNDER SLABS | |
| -SPANNING UP TO 4500 | 7 DAYS |
| -SPANNING OVER 4500 | 14 DAYS |
| * REMOVAL OF PROPS UNDER BEAMS | |
| -SPANNING UP TO 6000 | 14 DAYS |
| -SPANNING OVER 6000 | 21 DAYS |

CONCRETE :-

- C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
- C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
- C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ldt-550	Ldc-550	Ldt-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-

- R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786-2008.
 - R2. REFER TO HIGH YIELD STRENGTH DEFORMED BARS WITH CHARACTERSTIC STRENGTH OF 550D N/mm².
 - R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

DESIGN DATA :-

- (1). GRADE OF CONCRETE SHALL BE-
 - * FOUNDATION -M-25
 - * COLUMNS - AS/SCHEDULES
 - * ROOF - M-25
- (2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS

NO.	DATE	ISSUED TO	CKD.
-----	------	-----------	------

PROJECT

PROPOSED BUILDING AT PLOT NO. F-28, F-29 & F-30, 6-D ENGINEERS COLONY , JAIPUR

DRAWING TITLE






FIRST TO FIFTH FLOOR
SHUTTERING LAYOUT PLAN

DRAWN BY: DEEPAK

CHECKED BY: HEMANT
KACHHWAHA

DATE: 25.02.2025

REMARK:



For Parth Sarthi Build Estate (P) Ltd.
मेधा 12m
Director

Er. Hemant Kachhwaha
M.Tech(Str) B.E.(Civil)
S.K. CREATIONS
Hemant Kachhwaha
Proprietor/Manager

GRADE OF CONCRETE M-25
GRADE OF STEEL FE - 550D

STRUCTURE CONSULTANT
S.K. CREATIONS
67, GAYTRI NAGAR-A, DURGAPURA, JAIPUR
(RAJASTHAN) 302018
Email -skcreations.hk@gmail.com
MO. +91-9351388735

ARCHITECTS
FRANK SQUARE
ARCHITECTURE | PLANNER | DESIGNER
C-49 VIDYA APARTMENT PARAS MARG,
BAPU NAGAR JAIPUR, (RAJ.)
Email-afranksquare@gmail.com
Mobile-9461302542

GENERAL NOTES :-
(1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
(2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
(3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-
(1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
(2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE DUE TO EARTHQUAKES.
(3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-
P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL, SAND WITHOUT GRAVEL AND PEBBLES.
P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES
P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS
* WALLS, COLUMNS AND VERTICAL FACES OF ALL MEMBERS 36 TO 48 HOURS
* SLABS (PROPS LEFT UNDER) 3 DAYS
* BEAM SOFFITS (PROPS LEFT UNDER) 7 DAYS
* REMOVAL OF PROPS UNDER SLABS
-SPANNING UP TO 4500 7 DAYS
-SPANNING OVER 4500 14 DAYS
* REMOVAL OF PROPS UNDER BEAMS
-SPANNING UP TO 6000 14 DAYS
-SPANNING OVER 6000 21 DAYS

CONCRETE :-
C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ldt-550	Ldc-550	Ldt-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-
R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786-2008.
R2. REFER TO HIGH YIELD STRENGTH DEFORMED BARS WITH CHARACTERSTIC STRENGTH OF 550D N/mm².
R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
* FOUNDATION 50 mm. ALL AROUND
* COLUMNS 40 mm. ALL AROUND
* BEAMS 30 mm. ALL AROUND
* SLABS 20 mm. TOP & BOTTOM
* WALLS 25 mm. EARTH FACE
* WALLS 20 mm. INNER FACE

DESIGN DATA :-
(1). GRADE OF CONCRETE SHALL BE-
* FOUNDATION -M-25
* COLUMNS - AS/SCHEDULES
* ROOF - M-25
(2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS

NO.	DATE	ISSUED TO	CKD.



PROJECT
PROPOSED BUILDING AT PLOT NO. F-28, F-29 & F-30, 6-D ENGINEERS COLONY , JAIPUR

DRAWING TITLE
STILT TO FIRST FLOOR
STAIR CASE DETAIL

DRAWN BY: DEEPAK
CHECKED BY: HEMANT KACHHWAHA

DATE: 20.02.2025

REMARK:



TYP.BAR CURTAILMENT IN SLAB

For Parth Sarthi Build Estate (P) Ltd.

Director

Er. Hemant Kachhwaha

M.Tech(Str) B.E.(Civil)

For S.K. CREATIONS

Proprietor/Manager

GRADE OF CONCRETE M-25
GRADE OF STEEL FE - 550D

R.C.C. SLAB DETAILS:-

SLAB NO.	SHORT SPAN	LONG SPAN	CRANK BAR	THICK	GRADE
S1	#8@5"C/C	#8@5"C/C	#8@7"C/C	0'-6"	M-25
S2	#10@6"C/C	#8@6"C/C	#8@7"C/C	0'-6"	M-25
S3	#10@4"C/C	#10@6"C/C	#8@7"C/C	0'-6"	M-25
S4	#10@4"C/C	#10@4"C/C	#8@7"C/C	0'-6"	M-25

STRUCTURE CONSULTANT

S.K. CREATIONS

67, GAYTRI NAGAR-A, DURGAPURA,JAIPUR
(RAJASTHAN) 302018
Email -skcreations.hk@gmail.com
MO. +91-9351388735

ARCHITECTS

FRANK SQUARE

ARCHITECTURE | PLANNER | DESIGNER
C-49 VIDYA APARTMENT PARAS MARG,
BAPU NAGAR JAIPUR, (RAJ.)
Email-affranksquare@gmail.com
Mobile-9461302542

GENERAL NOTES :-

- (1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- (2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- (3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-

- (1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- (2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE DUE TO EARTHQUAKES.
- (3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-

- P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
 - P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL,SAND WITHOUT GRAVEL AND PEBBLES.
 - P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES.
 - P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
 - P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS
- | | |
|--|----------------|
| * WALLS, COLUMNS AND VERTICAL FACES OF ALL MEMBERS | 36 TO 48 HOURS |
| * SLABS (PROPS LEFT UNDER) | 3 DAYS |
| * BEAM SOFFITS (PROPS LEFT UNDER) | 7 DAYS |
| * REMOVAL OF PROPS UNDER SLABS | |
| -SPANNING UP TO 4500 | 7 DAYS |
| -SPANNING OVER 4500 | 14 DAYS |
| * REMOVAL OF PROPS UNDER BEAMS | |
| -SPANNING UP TO 6000 | 14 DAYS |
| -SPANNING OVER 6000 | 21 DAYS |

CONCRETE :-

- C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
- C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
- C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ldt-550	Ldc-550	Ldt-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-

- R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786-2008.
 - R2. REFER TO HIGH YIELD STRENGTH DEFORMED BARS WITH CHARACTERSTIC STRENGTH OF 550D N/mm².
 - R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

DESIGN DATA :-

- (1). GRADE OF CONCRETE SHALL BE-
 - * FOUNDATION -M-25
 - * COLUMNS - AS/SCHEDULES
 - * ROOF - M-25
- (2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS

NO.	DATE	ISSUED TO	CKD.
-----	------	-----------	------

PROJECT

PROPOSED BUILDING AT PLOT NO. F-28, F-29 & F-30, 6-D ENGINEERS COLONY , JAIPUR

DRAWING TITLE

SIXTH FLOOR SHUTTERING
DETAIL

DRAWN BY: DEEPAK

CHECKED BY: HEMANT
KACHHWAHA

DATE: 02.07.2025

REMARK:

STRUCTURE CONSULTANT

S.K. CREATIONS

67, GAYTRI NAGAR-A, DURGAPURA, JAIPUR

(RAJASTHAN) 302018

Email -skcreations.hk@gmail.com

MO. +91-9351388735

ARCHITECTS

FRANK SQUARE

ARCHITECTURE | PLANNER | DESIGNER

C-49 VIDYA APARTMENT PARAS MARG,

BAPU NAGAR JAIPUR, (RAJ.)

Email-afranksquare@gmail.com

Mobile-9461302542

GENERAL NOTES :-

- (1). DO NOT SCALE THIS DRAWING FOLLOW WRITTEN DIMENSIONS ONLY.
- (2). ANY DISCREPANCY IN THE DRAWING SHOULD BE IMMEDIATELY BROUGHT TO THE NOTICE OF ARCHITECT, PRIOR TO THE CONSTRUCTION.
- (3). BAD WORKMANSHIP WILL BE SOLE RESPONSIBILITY OF CLIENT & CONTRACTOR.

EXCAVATION CHECK :-

- (1). THE PROPER SOIL INVESTIGATION HAS BEEN CARRIED OUT FOR DETERMINING THE SAFE BEARING CAPACITY.
- (2). THE SOIL SHOULD NOT LIABLE TO LIQUEFACTION DUE DUE TO EARTHQUAKES.
- (3). THE SOIL SHOULD NOT LIABLE TO LANDSLIDE HAZARD.

CONSTRUCTION PRACTICE :-

- P1. IT IS MANDATORY TO REMOVE ALL LOOSE SOIL TILL THE FIRM SOIL IS REACHED.
- P2. BACK FILLING AROUND THE FOUNDATIONS SHALL BE CARRIED OUT USING SOIL, SAND WITHOUT GRAVEL AND PEBBLES.
- P3. IT IS ADVISABLE TO ALLOW STANDING WATER IN THE EXCAVATION TRENCHES FOR 24 HOURS. WHEN THE SURFACE IS SEMIDRY, HAND RAMMING SHALL BE CARRIED OUT WITH AT LEAST 6 TO 8 PASSES
- P4. BACK FILLING OF BASEMENT WALLS SHALL BE DONE ONLY AFTER THE ROOF SLAB HAS BEEN DEPROPPED.
- P5. IN NORMAL CIRCUMSTANCES AND WHERE ORDINARY PORTLAND CEMENT IS USED, FORMS MAY GENERALLY BE REMOVED AFTER THE EXPIRY OF THE FOLLOWING PERIODS
- | | |
|--|----------------|
| * WALLS, COLUMNS AND VERTICAL FACES OF ALL MEMBERS | 36 TO 48 HOURS |
| * SLABS (PROPS LEFT UNDER) | 3 DAYS |
| * BEAM SOFFITS (PROPS LEFT UNDER) | 7 DAYS |
| * REMOVAL OF PROPS UNDER SLABS | |
| -SPANNING UP TO 4500 | 7 DAYS |
| -SPANNING OVER 4500 | 14 DAYS |
| * REMOVAL OF PROPS UNDER BEAMS | |
| -SPANNING UP TO 6000 | 14 DAYS |
| -SPANNING OVER 6000 | 21 DAYS |

CONCRETE :-

- C1. USE CONCRETE GRADE M-25 FOR COLUMNS & M-25 FOR OTHERS
- C2. ALL RCC. WORK SHALL BE CARRIED OUT AS PER IS-456-2000.
- C3. DEVELOPMENT LENGTH FOR $F_y = 550 \text{ N/mm}^2$ & 415 N/mm^2

CONC. GRADE	Ltd-550	Ldc-550	Ltd-415	Ldc-415
M-20	57Ø	46Ø	47Ø	38Ø
M-25	49Ø	39Ø	41Ø	33Ø
M-30	46Ø	37Ø	38Ø	31Ø
M-35	41Ø	33Ø	34Ø	27Ø
M-40	36Ø	29Ø	30Ø	24Ø

REINFORCING STEEL :-

- R1. ALL REINFORCING STEEL WILL BE OF TESTED QUALITY CONFORMING TO IS:1786:2008.
- R2. REFER TO HIGH YIELD STRENGTH DEFORMED BARS WITH CHARACTERSTIC STRENGTH OF 550D N/mm².
- R3. CLEAR COVER TO MAIN REINFORCEMENT SHALL BE
- | | |
|--------------|---------------------|
| * FOUNDATION | 50 mm. ALL AROUND |
| * COLUMNS | 40 mm. ALL AROUND |
| * BEAMS | 30 mm. ALL AROUND |
| * SLABS | 20 mm. TOP & BOTTOM |
| * WALLS | 25 mm. EARTH FACE |
| * WALLS | 20 mm. INNER FACE |

DESIGN DATA :-

- (1). GRADE OF CONCRETE SHALL BE-
 - * FOUNDATION -M-25
 - * COLUMNS - AS/SCHEDULES
 - * ROOF - M-25
- (2). GRADE OF STEEL SHALL BE- FE 550D

REVISIONS

NO.	DATE	ISSUED TO	CKD.

PROJECT

PROPOSED BUILDING AT PLOT NO. F-28, F-29 & F-30, 6-D ENGINEERS COLONY, JAIPUR

DRAWING TITLE

SIXTH FLOOR BEAM DETAIL

DRAWN BY: DEEPAK

CHECKED BY: HEMANT KACHHWAHA

DATE: 02.07.2025

REMARK:

